



DST10100S-A



## Pin out



## Description

Littelfuse DST series Ultra Low  $V_F$  Schottky Barrier Rectifier is designed to meet the general requirements of commercial and industrial applications by providing high temperature, low leakage and lower  $V_F$  products.

It is suitable for high frequency switching mode power supply, free-wheeling diodes and polarity protection diodes.

## Features

- High reliability application and AEC-Q101 qualified.
- Ultra low forward voltage drop
- High frequency operation
- MSL: Level 1 - unlimited
- High junction temperature capability
- Trench MOS Schottky technology
- Single die in TO-277B Package
- Pb-free E3 means 2nd level interconnect is Pb-free and the terminal finish material is tin(Sn) (IPC/ JEDEC J-STD-609A.01)

## Applications

- Switching mode power supply
- DC/DC converters
- Free-Wheeling diodes
- Polarity Protection Diodes

## Maximum Ratings

| Parameters                          | Symbol      | Test Conditions                                                     | Max | Unit |
|-------------------------------------|-------------|---------------------------------------------------------------------|-----|------|
| Peak Inverse Voltage                | $V_{RWM}$   | -                                                                   | 100 | V    |
| Single Peak Reverse Voltage         | $V_{RSM}$   | -                                                                   | 105 | V    |
| Average Forward Current*            | $I_{F(AV)}$ | 50% duty cycle @ $T_L = 125^\circ\text{C}$<br>rectangular wave form | 10  | A    |
| Peak One Cycle Non-Repetitive Surge | $I_{FSM}$   | 8.3 ms, half Sine pulse                                             | 150 | A    |

\* Mounted on 30 mm x 30 mm pad areas aluminum PCB

## Electrical Characteristics

| Parameters             | Symbol   | Test Conditions                                         | Max  | Unit |
|------------------------|----------|---------------------------------------------------------|------|------|
| Forward Voltage Drop * | $V_{F1}$ | @2A, Pulse, $T_J = -40^\circ\text{C}$                   | 0.60 | V    |
|                        | $V_{F2}$ | @5A, Pulse, $T_J = -40^\circ\text{C}$                   | 0.65 |      |
|                        | $V_{F3}$ | @10A, Pulse, $T_J = -40^\circ\text{C}$                  | 0.70 |      |
|                        | $V_{F4}$ | @2A, Pulse, $T_J = 25^\circ\text{C}$                    | 0.50 |      |
|                        | $V_{F5}$ | @5A, Pulse, $T_J = 25^\circ\text{C}$                    | 0.60 |      |
|                        | $V_{F6}$ | @10A, Pulse, $T_J = 25^\circ\text{C}$                   | 0.70 |      |
|                        | $V_{F7}$ | @2A, Pulse, $T_J = 125^\circ\text{C}$                   | 0.40 |      |
|                        | $V_{F8}$ | @5A, Pulse, $T_J = 125^\circ\text{C}$                   | 0.55 |      |
|                        | $V_{F9}$ | @10A, Pulse, $T_J = 125^\circ\text{C}$                  | 0.65 |      |
| Reverse Current *      | $I_{R1}$ | @ $V_R = \text{rated } V_R$ , $T_J = 25^\circ\text{C}$  | 0.25 | mA   |
|                        | $I_{R2}$ | @ $V_R = \text{rated } V_R$ , $T_J = 125^\circ\text{C}$ | 36   |      |

\* Pulse Width < 300 $\mu\text{s}$ , Duty Cycle < 2%

## Thermal-Mechanical Specifications

| Parameters                                        | Symbol       | Test Conditions | Max         | Unit |
|---------------------------------------------------|--------------|-----------------|-------------|------|
| Junction Temperature                              | $T_J$        |                 | -55 to +150 | °C   |
| Storage Temperature                               | $T_{stg}$    |                 | -55 to +150 | °C   |
| Maximum Thermal Resistance<br>Junction to Ambient | $R_{thJA}$   | DC operation    | 75          | °C/W |
| Maximum Thermal Resistance<br>Junction to Lead    | $R_{thJL}^*$ |                 | 3.5         | °C/W |
| Approximate Weight                                | wt           |                 | 0.08        | g    |
| Case Style                                        | TO-277B      |                 |             |      |

\*Lead temperature monitored at the cathode pin

Figure 1: Forward Current Derating Curve




Figure 2: Forward Power Loss Characteristics




Figure 3: Typical Forward Characteristics







Figure 4: Typical Reverse Characteristics




**Figure 5: Typical Junction Capacitance**



**Dimensions-TO-277B**




**Mounting Pad Layout**



| Symbol | Millimeters |      |      |
|--------|-------------|------|------|
|        | Min         | Typ  | Max  |
| A      | 6.30        | 6.50 | 6.70 |
| B      | 5.28        | 5.38 | 5.48 |
| C      | 3.88        | 3.98 | 4.08 |
| D      | 2.90        | 3.05 | 3.20 |
| E      | 3.40        | 3.55 | 3.70 |
| F      | 4.20        | 4.40 | 4.60 |
| G      | 1.70        | 1.80 | 1.90 |
| I      | 1.74        | 1.84 | 1.94 |
| J      | 0.65        | 0.85 | 1.05 |
| K      | 0.85        | 0.90 | 0.95 |
| L      | 0.95        | 1.10 | 1.25 |
| M      | 0.20        | 0.25 | 0.30 |
| N      | 0.25        | 0.40 | 0.55 |
| O      | 4.00        | 4.05 | 4.25 |

**Part Numbering and Marking System**




DST = Device Type  
 10 = Forward Current (10A)  
 100 = Reverse Voltage (100V)  
 S = Package Type  
 A = AEC-Q101 qualified device  
 LF = Littelfuse  
 YY = Year  
 WW = Week  
 L = Lot Number

### Packing Options

| Part Number | Marking     | Packing Mode   | M.O.Q |
|-------------|-------------|----------------|-------|
| DST10100S-A | DST10100S-A | 5000pcs / Reel | 5000  |

### Carrier Tape & Reel Specification



| Symbol | Millimeters |       |
|--------|-------------|-------|
|        | Min         | Max   |
| A      | 4.28        | 4.48  |
| B      | 6.80        | 7.00  |
| d      | 1.40        | 1.60  |
| d1     | -           | 1.50  |
| E      | 1.65        | 1.85  |
| F      | 7.40        | 7.60  |
| P      | 5.40        | 5.60  |
| P0     | 3.90        | 4.10  |
| W      | 11.70       | 12.30 |

#### Disclaimer Notice

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at <http://www.littelfuse.com/disclaimer-electronics>.



Part of:

