



DENAN PRODUCT CERTIFICATE

Certificate Number: NBK250703-E10480A
DUPLICATE

Issue Date: July 25, 2002
Revised Date:
Expiration Date: July 24, 2009
Page 1 of 2

Representative sample(s) of the Specified Product(s) (as defined by the Japanese Ministry of Economy, Trade and Industry) has/have been found to comply with Technical Requirements stipulated in the Electrical Appliance and Material Safety Law, Article 8, Paragraph 1 and the requirements stipulated by the Ministerial Ordinance of the Law, Article 9, Paragraph 2 (limited to inspections relating to the Law, Article 9, Paragraph 1, Item 2) by the Conformity Assessment Body as listed below:

File No.: E10480

Applicant: Littelfuse Inc.
800 E. Northwest Highway
Des Plaines, IL 60016 U.S.A.

Manufacturer: Suzhou Littelfuse OVS Ltd.
Suzhou Industrial Park
6 Xinghai St.
Suzhou Jiangsu 215021 CHINA

Factory: Same as Manufacturer

Product Name: Miniature Fuses (Specified Product)

Type Classification: Refer to Attachment

Standard Used: DENAN Technical Requirements Ministerial Ordinance Paragraph 2
J60127-1 (H14) and J60127-2 (H14)


Conformity Assessment Method: DENAN Technical Requirements & DENAN Enforcement Regulations Appendix 4

CAB ID: UL-US

CAB: Underwriters Laboratories Inc.
333 Pfingsten Road
Northbrook, Illinois 60062 U.S.A.

This DENAN Product Certificate does not indicate acceptability of the product(s) for Listing, Classification or Recognition by Underwriters Laboratories Inc. Products marked with CAB ID must comply with the DENAN Law / Standards.

Verification Staff:


Maria Mueller, Associate Manager
International Compliance Services

Aug-13-2002 08:00am

From-LITTELFUSE, INC PROD & TECH DEV.

+8473910998

T-976 P.011/021 F-743



DENAN PRODUCT CERTIFICATE

Attachment 1

Certificate Number: NBK250702-E10480A

Issue Date:

Rev. No.

July 25, 2002

Revised Date:

Expiration Date:

July 24, 2009

Page 2 of 2

| Factor | Classification |
|--|--|
| Rated voltage | Exceeding 125V |
| Rated current | 5A or less |
| Fuse element material | Silver |
| Number of fuse element | One |
| Filler material | With filler material |
| Cartridge material (excluding inner cartridge) | Ceramic or glass |
| Terminal | Ferruled terminal |
| Vent holes | Without vent holes |
| Blown-fuse indicator | Without blown-fuse indicator |
| Application | For use in electronic devices |
| Rated interrupting current | Exceeding 1,000A, and less than or equal to 1,500A |