| LEGEND | | |
|---|---|---|
| BLACK | C | HIGH BEAM |
| ORANGE | B | LOW BEAM |
| YELLOW | A | BAT 12V |
| WIRE COLOR | POSTION | POSTION |




NOTES:
1. ALL STEEL PARTS PLATED
2. ALL DIMENSIONS ARE REFERENCE ONLY
3. EACH DOWNWARD STROKE OF THE PLUNGER SHIFTS BEAMS. SWITCH MUST CHANGE CIRCUIT FROM ONE TERMINAL TO THE OTHER WITHOUT LOSS OF LIGHT PERCEPTIBLE TO THE EYE
4. WIRES HOT STAMED WITH IDENTIFICATION CODES
5. LABEL INCLUDES COLE HERSEE PART NUMBER, REVISION LEVEL & COLE HERSEE NAME OR LOGO

***Revision Control Record***

| Rev. | Description of Change | ECN No. | Date |
|---|---|---|---|
| F | SHOW TEXT ON CAP | 02058 | 02/07/02 |
| G | LOOM MFG & PN | 08234 | 04/24/08 |
| H | BOM CHANGE | 17764 | 07/10/17 |

| Rev. | Description of Change | ECN No. | Date |
|---|---|---|---|
| | | | |

**Note:** unless noted otherwise all dimension are AFTER plating
**Tolerances:** Unless otherwise specifically noted, the following are default tolerances;

| 2-places | 3-places | Angular |
|---|---|---|
| ± 0.02 [0.5] | ± 0.005 [0.13] | ± 1° |

Unless otherwise specified dimensions are in inches. Dimensions in brackets [ ] are in millimeters.
"REF" = Non-Toleranced Reference Dimension, shown for clarification purposes only.
Note: *All tolerances are Non-Cumulative.*

**PROPRIETARY INFORMATION**
All information contained herein, is proprietary to the Cole Hersee Company. Unauthorized use or reproduction is prohibited.

3RD ANGLE PROJECTION

**Special Characteristics:**
- CC — Critical Characteristic, relating to Safety and/or Regulatory Compliance
- X — Significant Characteristic relating to Process Control
- KC — Control Dimension relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer

Littelfuse®
Phn: 617-268-2100 Web: www.colehersee.com

**Description:** DIMMER SWITCH

**Drawing / Part No.:** 7786-03

**Current Rev.** H

FORM CHT-6 (1/12) | Used On or Ref.: -- | Scale: 1:1 | Drawn BY: RT | Date Drawn: 01/18/00 | Pg. 1 of 1