


# X2-Class HiPerFET™ Power MOSFET

## IXFA34N65X2


$$\begin{aligned} V_{DSS} &= 650V \\ I_{D25} &= 34A \\ R_{DS(on)} &\leq 100m\Omega \end{aligned}$$

N-Channel Enhancement Mode  
Avalanche Rated



| Symbol     | Test Conditions                                                          | Maximum Ratings    |                             |
|------------|--------------------------------------------------------------------------|--------------------|-----------------------------|
| $V_{DSS}$  | $T_J = 25^\circ\text{C}$ to $150^\circ\text{C}$                          | 650                | V                           |
| $V_{DGR}$  | $T_J = 25^\circ\text{C}$ to $150^\circ\text{C}$ , $R_{GS} = 1M\Omega$    | 650                | V                           |
| $V_{GSS}$  | Continuous                                                               | $\pm 30$           | V                           |
| $V_{GSM}$  | Transient                                                                | $\pm 40$           | V                           |
| $I_{D25}$  | $T_C = 25^\circ\text{C}$                                                 | 34                 | A                           |
| $I_{DM}$   | $T_C = 25^\circ\text{C}$ , Pulse Width Limited by $T_{JM}$               | 68                 | A                           |
| $I_A$      | $T_C = 25^\circ\text{C}$                                                 | 10                 | A                           |
| $E_{AS}$   | $T_C = 25^\circ\text{C}$                                                 | 1                  | J                           |
| $dv/dt$    | $I_S \leq I_{DM}$ , $V_{DD} \leq V_{DSS}$ , $T_J \leq 150^\circ\text{C}$ | 50                 | V/ns                        |
| $P_D$      | $T_C = 25^\circ\text{C}$                                                 | 540                | W                           |
| $T_J$      |                                                                          | -55 ... +150       | $^\circ\text{C}$            |
| $T_{JM}$   |                                                                          | 150                | $^\circ\text{C}$            |
| $T_{stg}$  |                                                                          | -55 ... +150       | $^\circ\text{C}$            |
| $T_L$      | Maximum Lead Temperature for Soldering                                   | 300                | $^\circ\text{C}$            |
| $dT/dt$    | Heating / Cooling rate, $175^\circ\text{C} - 210^\circ\text{C}$          | 50                 | $^\circ\text{C}/\text{min}$ |
| $T_{SOLD}$ | 1.6 mm (0.062in.) from Case for 10s                                      | 260                | $^\circ\text{C}$            |
| $F_C$      | Mounting Force                                                           | 10..65 / 2.2..14.6 | N/lb                        |
| Weight     |                                                                          | 2.5                | g                           |

TO-263



G = Gate      D = Drain  
S = Source      Tab = Drain

### Features

- International Standard Package
- Low  $R_{DS(ON)}$  and  $Q_G$
- Avalanche Rated
- Low Package Inductance

### Advantages

- High Power Density
- Easy to Mount
- Space Savings


### Applications

- Switch-Mode and Resonant-Mode Power Supplies
- DC-DC Converters
- PFC Circuits
- AC and DC Motor Drives
- Robotics and Servo Controls

| Symbol       | Test Conditions                                                 | Characteristic Values |      |                       |
|--------------|-----------------------------------------------------------------|-----------------------|------|-----------------------|
|              | ( $T_J = 25^\circ\text{C}$ , Unless Otherwise Specified)        | Min.                  | Typ. | Max.                  |
| $BV_{DSS}$   | $V_{GS} = 0V$ , $I_D = 1mA$                                     | 650                   |      | V                     |
| $V_{GS(th)}$ | $V_{DS} = V_{GS}$ , $I_D = 2.5mA$                               | 3.5                   |      | 5.0 V                 |
| $I_{GSS}$    | $V_{GS} = \pm 30V$ , $V_{DS} = 0V$                              |                       |      | $\pm 100$ nA          |
| $I_{DSS}$    | $V_{DS} = V_{DSS}$ , $V_{GS} = 0V$<br>$T_J = 125^\circ\text{C}$ |                       |      | 10 $\mu A$<br>1.75 mA |
| $R_{DS(on)}$ | $V_{GS} = 10V$ , $I_D = 0.5 \cdot I_{D25}$ , Note 1             |                       |      | 100 m $\Omega$        |

| Symbol                                              |                                                                                                           | Test Conditions                                                                                                                              |      | Characteristic Values |  |  |
|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|------|-----------------------|--|--|
| (T <sub>J</sub> = 25°C, Unless Otherwise Specified) |                                                                                                           | Min.                                                                                                                                         | Typ. | Max                   |  |  |
| g <sub>fs</sub>                                     | V <sub>DS</sub> = 10V, I <sub>D</sub> = 0.5 • I <sub>D25</sub> , Note 1                                   | 12                                                                                                                                           | 20   | S                     |  |  |
| R <sub>Gi</sub>                                     | Gate Input Resistance                                                                                     |                                                                                                                                              | 0.8  | Ω                     |  |  |
| C <sub>iss</sub>                                    | V <sub>GS</sub> = 0V, V <sub>DS</sub> = 25V, f = 1MHz                                                     |                                                                                                                                              | 3230 | pF                    |  |  |
| C <sub>oss</sub>                                    |                                                                                                           |                                                                                                                                              | 2000 | pF                    |  |  |
| C <sub>rss</sub>                                    |                                                                                                           |                                                                                                                                              | 2    | pF                    |  |  |
| Effective Output Capacitance                        |                                                                                                           |                                                                                                                                              |      |                       |  |  |
| C <sub>o(er)</sub>                                  | Energy related                                                                                            | V <sub>GS</sub> = 0V<br>V <sub>DS</sub> = 0.8 • V <sub>DSS</sub>                                                                             | 130  | pF                    |  |  |
| C <sub>o(tr)</sub>                                  | Time related                                                                                              |                                                                                                                                              | 486  | pF                    |  |  |
| t <sub>d(on)</sub>                                  | Resistive Switching Times                                                                                 | V <sub>GS</sub> = 10V, V <sub>DS</sub> = 0.5 • V <sub>DSS</sub> , I <sub>D</sub> = 0.5 • I <sub>D25</sub><br>R <sub>G</sub> = 10Ω (External) | 37   | ns                    |  |  |
| t <sub>r</sub>                                      |                                                                                                           |                                                                                                                                              | 60   | ns                    |  |  |
| t <sub>d(off)</sub>                                 |                                                                                                           |                                                                                                                                              | 64   | ns                    |  |  |
| t <sub>f</sub>                                      |                                                                                                           |                                                                                                                                              | 30   | ns                    |  |  |
| Q <sub>g(on)</sub>                                  | V <sub>GS</sub> = 10V, V <sub>DS</sub> = 0.5 • V <sub>DSS</sub> , I <sub>D</sub> = 0.5 • I <sub>D25</sub> |                                                                                                                                              | 56   | nC                    |  |  |
| Q <sub>gs</sub>                                     |                                                                                                           |                                                                                                                                              | 19   | nC                    |  |  |
| Q <sub>gd</sub>                                     |                                                                                                           |                                                                                                                                              | 18   | nC                    |  |  |
| R <sub>thJC</sub>                                   |                                                                                                           |                                                                                                                                              |      | 0.23 °C/W             |  |  |

## TO-263 (IXFA) Outline



- 1 = Gate  
2 = Drain  
3 = Source  
4 = Drain

| SYM | INCHES   |      | MILLIMETERS |       |
|-----|----------|------|-------------|-------|
|     | MIN      | MAX  | MIN         | MAX   |
| A   | .160     | .190 | 4.06        | 4.83  |
| A1  | .080     | .110 | 2.03        | 2.79  |
| b   | .020     | .039 | 0.51        | 0.99  |
| b2  | .045     | .055 | 1.14        | 1.40  |
| c   | .016     | .029 | 0.40        | 0.74  |
| c2  | .045     | .055 | 1.14        | 1.40  |
| D   | .340     | .380 | 8.64        | 9.65  |
| D1  | .315     | .350 | 8.00        | 8.89  |
| E   | .380     | .410 | 9.65        | 10.41 |
| E1  | .245     | .320 | 6.22        | 8.13  |
| e   | .100 BSC |      | 2.54 BSC    |       |
| L   | .575     | .625 | 14.61       | 15.88 |
| L1  | .090     | .110 | 2.29        | 2.79  |
| L2  | .040     | .055 | 1.02        | 1.40  |
| L3  | .050     | .070 | 1.27        | 1.78  |
| L4  | 0        | .005 | 0           | 0.13  |

## Source-Drain Diode


| Symbol   | Test Conditions<br>( $T_J = 25^\circ\text{C}$ , Unless Otherwise Specified)    | Characteristic Values |      |               |
|----------|--------------------------------------------------------------------------------|-----------------------|------|---------------|
|          |                                                                                | Min.                  | Typ. | Max           |
| $I_S$    | $V_{GS} = 0\text{V}$                                                           |                       |      | 34 A          |
| $I_{SM}$ | Repetitive, pulse Width Limited by $T_{JM}$                                    |                       |      | 136 A         |
| $V_{SD}$ | $I_F = I_S$ , $V_{GS} = 0\text{V}$ , Note 1                                    |                       |      | 1.4 V         |
| $t_{rr}$ | $I_F = 17\text{A}$ , $-di/dt = 100\text{A}/\mu\text{s}$<br>$V_R = 100\text{V}$ |                       | 164  | ns            |
| $Q_{RM}$ |                                                                                |                       | 1.2  | $\mu\text{C}$ |
| $I_{RM}$ |                                                                                |                       | 14.4 | A             |

Notes: 1. Pulse test,  $t \leq 300\mu\text{s}$ , duty cycle,  $d \leq 2\%$ .


IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

|                                                                                  |           |           |           |           |             |             |             |             |             |             |
|----------------------------------------------------------------------------------|-----------|-----------|-----------|-----------|-------------|-------------|-------------|-------------|-------------|-------------|
| IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: | 4,835,592 | 4,931,844 | 5,049,961 | 5,237,481 | 6,162,665   | 6,404,065B1 | 6,683,344   | 6,727,585   | 7,005,734B2 | 7,157,338B2 |
|                                                                                  | 4,860,072 | 5,017,508 | 5,063,307 | 5,381,025 | 6,259,123B1 | 6,534,343   | 6,710,405B2 | 6,759,692   | 7,063,975B2 |             |
|                                                                                  | 4,881,106 | 5,034,796 | 5,187,117 | 5,486,715 | 6,306,728B1 | 6,583,505   | 6,710,463   | 6,771,478B2 | 7,071,537   |             |


**Fig. 1. Output Characteristics @  $T_J = 25^\circ\text{C}$**




**Fig. 2. Extended Output Characteristics @  $T_J = 25^\circ\text{C}$**




**Fig. 3. Output Characteristics @  $T_J = 125^\circ\text{C}$**




**Fig. 4.  $R_{DS(on)}$  Normalized to  $I_D = 17A$  Value vs. Junction Temperature**












**Fig. 5.  $R_{DS(on)}$  Normalized to  $I_D = 17A$  Value vs. Drain Current**



**Fig. 6. Normalized Breakdown & Threshold Voltages vs. Junction Temperature**



**Fig. 7. Maximum Drain Current vs. Case Temperature**

**Fig. 8. Input Admittance**

**Fig. 9. Transconductance**

**Fig. 10. Forward Voltage Drop of Intrinsic Diode**

**Fig. 11. Gate Charge**

**Fig. 12. Capacitance**


**Fig. 13. Output Capacitance Stored Energy**

**Fig. 14. Forward-Bias Safe Operating Area**

**Fig. 15. Maximum Transient Thermal Impedance**




---

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).