

HEAVY DUTY TIME DELAY BI-STABLE RELAY

Heavy Duty • 250A • 12V/24V



Description

The Heavy Duty Time Delay Bi-Stable Relay disconnects the battery from the vehicle electrical system with voltage self-recognition. It has immediate switch ON, controlled switch OFF, programmable delay time, and service state managing (service switch OFF and switch ON). The Heavy Duty Time Delay Bi-Stable Relay has a non-volatile memory, low battery alert system, and is thermal protected.

Features and Benefits

- UNECE R10 Rev05 compliant
- Built in TE Superseal connector 1.5 series
- · Remote command line for normal working (switch)
- Remote command line for SERVICE/EMERGENCY working (push button)
- NORMAL/SERVICE mode selection with power down restore
- Immunity to dirty switches
- Lamp driving line for error/status signaling

Applications

- Construction
- Military
- Transit
- Heavy Duty Truck
- Agriculture
- Engines with Selective Catalytic Reduction (SCR)

Web Resources

Download technical resources at:

littelfuse.com/hdtimedelay

Specifications

Amperage: 250A

Voltage Ratings: 12V/24V

Operating Temp: -40°C to 100°C

Ingress Protection: IP67 X9K

Color: Black

 Voltage Range:
 8.5V to 32V @ 23°C

 Max. Cranking Current:
 800A x 30 Sec.

 Max. Peak Current (S.C.):
 2000A x 5 Sec.

Light Line Current Rating: 1.3A continuous (6.5A protected)

Quiescent Current: 0.8mA @ 12V 1.5mA @ 24V

Input Active Line Current: 5mA @ 12V 10mA @ 24V

Programmable Delay Time: 1 Sec to 1 Hour

False Switch Status Immunity: Detected as open down to 2kohm
Detected as closed up to 25ohm

Ordering Information

PART NUMBER	DESCRIPTION
08070900	Programmable Time Delay Bi-Stable Relay

Recommended Products



Part Number: 00227066 Sealed Bi-Stable Position Switch with Cover and GREEN LED



Part Number: 00227068 Sealed Momentary Position Switch With Cover



Part Number: 00900400Bi-Stable Position
Switch BLACK



Part Number: 00900900 Momentary Position Switch RED



Part Number: 00901000 Momentary Position Switch GREEN





HEAVY DUTY TIME DELAY BI-STABLE RELAY

Heavy Duty • 250A • 12V/24V

Dimensions in millimeters



