



# PGB2 0201 Series

## Surface Mount Polymeric Electrostatic Discharge Suppressors



### Equivalent Circuits



### Product Characteristics

| Part Number  | Lines Protected | Component Package |
|--------------|-----------------|-------------------|
| PGB2010201KR | 1               | 0201              |

### Description

PULSE-GUARD® ESD Suppressors help protect sensitive electronic equipment against electrostatic discharge (ESD).

They use polymer composite materials to suppress fast-rising ESD transients (as specified in IEC 61000-4-2), while adding virtually no capacitance to the circuit.

They supplement the on-chip protection of integrated circuitry and are best suited for low-voltage, high-speed applications where low capacitance is important to ensure minimal interference of data signal integrity.

The new and ultra-small surface mount PGB2 0201 products offer a RoHS Compliant, Halogen Free, and 100% Lead Free circuit protection solution.

### Features & Benefits

- Lead-free, Halogen-free, and RoHS compliant
- Ultra-low capacitance
- Low leakage current
- Fast response time
- One line of protection
- Bi-directional
- Withstands multiple ESD strikes
- Compatible with pick-and-place processes

### Applications

- Antenna circuit
- Laptop / desktop computer
- Network hardware
- HDMI 1.3 / 1.4 / 2.0
- USB 3.2
- Computer peripherals
- Digital camera
- External storage
- Set-top box
- SATA and eSATA

### Electrical Characteristics

| Items                          | PGB 0201 |    |      |    |    | Unit   |
|--------------------------------|----------|----|------|----|----|--------|
|                                | 6        | 12 | 15   | 24 | 30 |        |
| Rated voltage (Max)            |          |    |      |    |    | V      |
| Leakage current                |          |    | 0.01 |    |    | μA     |
| Trigger voltage                |          |    | 300  |    |    | V      |
| Clamping voltage               |          |    | 20   |    |    | V      |
| Capacitance @1MHz              |          |    | 0.05 |    |    | pF     |
| IEC 61000-4-2 Direct Discharge |          |    | 8    |    |    | kV     |
| IEC 61000-4-2 Air Discharge    |          |    | 15   |    |    | kV     |
| Response time (Max)            |          |    | 1    |    |    | ns     |
| ESD withstand pulses           |          |    | 1000 |    |    | pulses |

# PGB2 0201 Series

## Surface Mount Polymeric Electrostatic Discharge Suppressors

### Environmental Specifications


| Item                          | Test Condition                           | Reference                 |
|-------------------------------|------------------------------------------|---------------------------|
| Operating Temperature         | -40 °C to 85 °C                          |                           |
| Bias Humidity                 | Rated voltage ,90%RH, 40 °C, 1000 hrs    | MIL-STD-202 Method 103    |
| Thermal Shock                 | -40 °C to 85 °C, 30 min. cycle, 5 cycles | JIS C 0025 (1998) Test Na |
| High Temperature Load Voltage | Rated voltage, 85 °C 1000 hrs            | MIL-STD-202G Method 108   |
| Solder Leach Resistance       | 260 °C 10s                               | MIL-STD-202G Method 210F  |

### Part Number List

| Part Number       | Rated Voltage (Max) |
|-------------------|---------------------|
| PGB2010201KR-06NR | 6 V                 |
| PGB2010201KR-12NR | 12 V                |
| PGB2010201KR-15NR | 15 V                |
| PGB2010201KR-24NR | 24 V                |
| PGB2010201KR-30NR | 30 V                |


### Soldering Parameters

|                                                                        |                                    |                         |
|------------------------------------------------------------------------|------------------------------------|-------------------------|
| <b>Reflow Condition</b>                                                |                                    | Pb-free assembly        |
| <b>Pre Heat</b>                                                        | - Temperature Min ( $T_{s(min)}$ ) | 150 °C                  |
|                                                                        | - Temperature Max ( $T_{s(max)}$ ) | 200 °C                  |
|                                                                        | - Time (Min to Max) ( $t_s$ )      | 60–180 seconds          |
| <b>Average Ramp-up Rate (Liquidus Temp (<math>T_L</math>) to peak)</b> |                                    | 5 °C / second max.      |
| <b><math>T_{s(max)}</math> to <math>T_L</math> - Ramp-up Rate</b>      |                                    | 5 °C / second max.      |
| <b>Reflow</b>                                                          | - Temperature ( $T_L$ ) (Liquidus) | 217 °C                  |
|                                                                        | - Temperature ( $t_L$ )            | 60–150 seconds          |
| <b>Peak Temperature (<math>T_p</math>)</b>                             |                                    | 250 <sup>+0/-5</sup> °C |
| <b>Time within 5°C of actual peak Temperature (<math>t_p</math>)</b>   |                                    | 20 – 40 seconds         |
| <b>Ramp-down Rate</b>                                                  |                                    | 5 °C / second max.      |
| <b>Time 25°C to peak Temperature (<math>T_p</math>)</b>                |                                    | 8 minutes max.          |




**PGB2 0201 Series****Surface Mount Polymeric Electrostatic Discharge Suppressors****Dimensions**



Unit: mm



| Chip Size   | L         | W         | H        | B          |
|-------------|-----------|-----------|----------|------------|
| <b>0201</b> | 0.62±0.05 | 0.32±0.03 | 0.3±0.05 | 0.165±0.05 |

**Recommended Landing Pad**

| Marking  | Unit (mm) |
|----------|-----------|
| <b>A</b> | 0.35±0.05 |
| <b>B</b> | 0.27±0.05 |
| <b>C</b> | 0.5±0.05  |

**PGB2 0201 Series****Surface Mount Polymeric Electrostatic Discharge Suppressors****Packaging, Tape and Reel Specifications**

| Marking | Unit (mm) |
|---------|-----------|
| A       | 178.0±2.0 |
| B       | 2.0±0.5   |
| C       | 13.0±0.5  |
| D       | 21.0±0.8  |
| E       | 62.0±1.5  |
| F       | 9.0±0.5   |
| G       | 13.0±1.0  |

| Marking | Unit (mm) |
|---------|-----------|
| A       | 8.00±0.30 |
| B       | 3.50±0.05 |
| C       | 1.75±0.05 |
| D       | 2.00±0.05 |
| E       | 4.00±0.10 |
| F       | 1.55±0.05 |
| L       | 0.68±0.02 |
| W       | 0.37±0.02 |
| T       | 0.42±0.02 |

| Part Number | Packaging Code | Quantity | Packaging Option        | Packaging Specification                             |
|-------------|----------------|----------|-------------------------|-----------------------------------------------------|
| PGB2010201  | KR             | 15000    | Tape and Reel (7" reel) | Carrier Tape: 8 mm, paper<br>Reel: 7" (178 mm) reel |

**Disclaimer Notice** - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at <http://www.littelfuse.com/disclaimer-electronics>.