



NOTES:

- RESISTOR: 620 OHMS ±5%.
1/2 WATT (METAL FILM).

METRIC

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN BRACKETS [] ARE INCHES
UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.
⊙ DENOTES CRITICAL CHARACTERISTICS.
CPK DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE
⊠ DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS
CP DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE

NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M
BILL OF MATERIAL				

LTR	DATE	REVISION	CHK	APD
D	10/16/97	38698C-REVISED & REDRAWN IN NEW STRUCTURE GNK		
E	04/24/02	82123D-CHG. TOLERANCES GNK		
F	11/26/02	82660B-CHG. CHARACTER INFO PJM		
G	09/07/07	85439D-REDRAWN IN UG, 4.3 WAS 4.6, 3.6 WAS 3.8 GMB		
H	09/01/09	001215EC-REMOVED ALL CPK MARKINGS GMB		
J	01/04/11	501388ECA-CHANGE BLACK HOT STAMP TO BLACK INK, OPL		
K	11/30/11	503801ECA-CHANGE DIMENSIONS, SEE ECO OPL		

COPIES TO	MATL SPEC
1 9	FINISH
2 10	DRW G. KERN
3 12	DATE 10/08/97
4 13	SCALE 4:1
5 14	DATE
6 15	CHK SUPER DR
7 16	DATE
8 17	APPD
9 18	FINISH GOOD WT
10 19	GRAMS/PIECE
11 20	
12 21	
13 22	
14 23	
15 24	
16 25	
17 26	
18 27	
19 28	
20 29	
21 30	
22 31	
23 32	
24 33	
25 34	
26 35	
27 36	
28 37	
29 38	
30 39	
31 40	
32 41	
33 42	
34 43	
35 44	
36 45	
37 46	
38 47	
39 48	
40 49	
41 50	

TOLERANCE UNLESS OTHERWISE SPECIFIED	
ONE PLACE DEC +/- .3	THREE PLACE DEC +/- .100
TWO PLACE DEC +/- .25	ANGULAR +/- 1°

3RD ANGLE PROJECTION	TITLE	RESISTOR ASSEMBLY
⊙	REVISION	DRWG. NO.
	K	02400106P
		OUTLINE