



NOTES:

1. RESISTOR: 500 OHMS ±5% 1/2 WATT (METAL FILM)

METRIC

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN BRACKETS [] ARE INCHES	UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.
⊙	DENOTES CRITICAL CHARACTERISTICS.
CPK	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE
ST	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS
CP	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE

NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M
BILL OF MATERIAL				

COPIES TO		MTRL SPEC	
1	9	FINISH	
2	10	DRW	DHM
3	12	CHK	DATE
4	13	APPD	DATE
5	14	SCALE 4:1	
6	15	SUPER DR	
7	16	FINISH GOOD WT	
8	17	GRAMS/PIECE	
18	18	TOLERANCE UNLESS OTHERWISE SPECIFIED	
19	19	THREE PLACE DEC +/- .100	
20	20	ANGULAR +/- 1°	
21	21	ONE PLACE DEC +/- .3	
22	22	TWO PLACE DEC +/- .25	
23	23	3RD ANGLE PROJECTION	
24	24	TITLE RESISTOR ASSEMBLY	
25	25	REVISION DRWG. NO. 02400118P	
26	26	OUTLINE	
27	27	LITTELFUSE DES PLAINES, ILLINOIS 60016	

LTR	DATE	REVISION	CHK	APD
A	08/16/06	62084-RELEASED DHM		
B	10/05/06	85080D-CHG. HOT STAMP FOIL FROM WHITE TO BLAVK DHM		
C	09/13/07	85439D-REDRAWN IN UG, 4.3 WAS 4.6, 3.6 WAS 3.8, 1.8 WAS 0.7 GMB		
D	01/04/11	50138BECA-CHANGE BLACK HOT STAMP TO BLACK INK. OPL		
E	11/30/11	503801ECA-CHANGE DIMENSIONS, SEE ECO OPL		