



% OF RATING	OPENING TIME	
	MINIMUM	MAXIMUM
100	100 HRS .	-
135	120 S	1800 S
200	10 S	300 S
350	1 S	15 S
600	0.3 S	5 S

INTERRUPT RATING: 2000A @ 32VDC
VOLTAGE RATING: 32VDC
TEMP. RATING: -40°C - 150°C

CABLE TYPE: IRRADIATED XLPE, MS-9502, YPES-25-08-245 (4AWG).
SPECIFICATION: MEETS LITTELFUSE'S VS-006013 SPECIFICATION
APPLICATION: DESIGNED FOR UNDERHOOD INSTALLMENT.

BAR CODE OR
DATE CODE: THE BAR CODE OR DATE CODE IS USED FOR LOT TRACEABILITY.
IT IS LOCATED ON ONE OF THE CABLE LEADS.

NO		COMPONENT NO		DESCRIPTION		QTY/M	U/M
BILL OF MATERIAL							
LTR		COPIES TO		MATERIAL SPEC		FINISH	
A		1	9 18	DRW	PJM	DATE	SCALE
B		2	10 19			DATE	FULL
C		3	12 20	CHK		DATE	SUPER DRW
D		4	13 21			DATE	
E		5	14 23	APPD		DATE	FINISH GOOD WT
F		6	15 33				GRAMS/PIECE
G		7	16 43			TOLERANCE UNLESS OTHERWISE SPECIFIED	
H		8	17 53			TWO PLACE DEC ±.25[.01] FRACTION ±	
I						THREE PLACE DEC ±.100[.004] ANGULAR ±1°	
J						TITLE	
K						CABLEPRO	
L							
M							
N							
O							
P							
Q							
R							
S							
T							
U							
V							
W							
X							
Y							
Z							
AA							
AB							
AC							
AD							
AE							
AF							
AG							
AH							
AI							
AJ							
AK							
AL							
AM							
AN							
AO							
AP							
AQ							
AR							
AS							
AT							
AU							
AV							
AW							
AX							
AY							
AZ							
BA							
BB							
BC							

UNLESS OTHERWISE SPECIFIED, DIMENSIONS IN BRACKETS ARE INCHES	1. DENOTES CRITICAL CHARACTERISTICS 2. DENOTES CPK DIMENSIONS - MINIMUM 3. DENOTES A CHARACTERISTIC THAT AFFECTS PROCESS PERFORMANCE. PROCEDURE OF INSPECTION AND TRACKING TO BE DEFINED IN THE SELFUSE INSPECTION INSTRUCTIONS 4. DENOTES CP DIMENSIONS - MINIMUM 5. BE WITHIN THE DIMENSIONAL TOLERANCE ON DRAWING AND INITIALLY APPROVED FOR MAXIMUM TOOL LIFE.
---	---