



NOTES:
 1. ALL STEEL PARTS PLATED
 2. ALL DIMENSIONS ARE REFERENCE ONLY
 3. SILVER CAD OXIDE CONTACT SURFACES
 4. O-RING SEAL BETWEEN MOUNTING STEM & CASE
 5. GASKET SEAL BETWEEN TERMINAL INSULATOR & CASE
 6. RATING:
 SWITCH MUST CARRY 1000 AMPS @ 6, 12, & 24 V DC FOR 1000 CYCLES OF
 30 SECONDS ON, 5 MINUTES OFF WITHOUT SIGNIFICANT DETERIORATION OF CONTACTS

Revision Control Record				Rev.	Description of Change	ECN No.	Date	Tolerances Unless otherwise specifically noted, the following are default tolerances:			PROPRIETARY INFORMATION This Engineering Drawing, and the information contained herein, is proprietary to Cole Hersee Company and may not be disclosed, re-produced, or in any other way transferred or communicated to any other party without the express written consent of an authorized representative of Cole Hersee Company.	Special Characteristics:		Cole Hersee Co. 20 Old Colony Ave., South Boston, MA, 02127 Phn: 617-268-2100 Web: www.colehersee.com	
Rev.	Description of Change	ECN No.	Date					2-places +/- 0.02"	3-places +/- 0.005"	Angular +/- 1°		<input type="checkbox"/> Critical Characteristic, relating to Safety and/or Regulatory Compliance <input checked="" type="checkbox"/> Significant Characteristic relating to Process Control <input type="checkbox"/> Control Dimension relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer	Description:		Current Rev.
H	REDRAWN; BOM CHANGE	10150	4/29/10									<input checked="" type="checkbox"/> Critical Characteristic, relating to Safety and/or Regulatory Compliance <input checked="" type="checkbox"/> Significant Characteristic relating to Process Control <input type="checkbox"/> Control Dimension relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer	SWITCH, MASTER DISCONNECT	H	
								FORM CHT-6 (2/07)	Used On or Ref.: 2484-A WITH WELDED CASE & KEY	Scale: 1:1	Drawn BY: RMT	Date Drawn: 12/12/79	Pg. 1 of 1	2484-19	