| REVISION | | |
|---|---|---|
| REV | DATE | DESCRIPTION |
| A | 8/26/22 | 525614GCP - RELEASE MRY |




| 1 | | | | |
|---|---|---|---|---|
| NO | COMPONENT NO | DESCRIPTION | QTY/M | U/M |

BILL OF MATERIAL

| | |
|---|---|
| <S> | CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE |
| ● | DENOTES CRITICAL CHARACTERISTICS. |
| CPK | DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE |
| ⟨ST⟩ | DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS. |
| CP | DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE. |

B

| MATL SPEC | | FINISH | |
|---|---|---|---|
| DRW<br>JMOLER | DATE<br>8/22/2022 | SCALE<br>NTS | FINISH GOOD WT<br>GRAMS/PIECE |

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN BRACKETS [ ] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994

3RD ANGLE PROJECTION

**TITLE**

3PH39P18MM OUTLINE

Littelfuse®
CHICAGO, ILLINOIS 60631

| REVISION | DRWG NO. | SHEET 1 OF 1 |
|---|---|---|
| A | OL-3PH39P18MM | |