

B

B

A

A

48540-01	12.7	13.2	25.4	26.4	8.5	34.0	120	60	1	12805
48540	12.7	13.2	25.4	26.4	8.5	34.0	120	60	1	NONE
COLE HERSEE PART NUMBER	12V System Disconnect Threshold	12V System Connect Threshold	24V System Disconnect Threshold	24V System Connect Threshold	System Under-Voltage Threshold	System Over-Voltage Threshold	Connect Time Delay (seconds)	Disconnect Time Delay (seconds)	Boost Timeout (minutes)	KIT

Revision Control Record				Rev.	Description of Change	ECN No.	Date	Tolerances Unless otherwise specifically noted, the following are default tolerances; 2-places 3-places Angular +/- 0.02" +/- 0.005" +/- 1" Metric: Shown in [] refers to equivalent English Dim Tol "REF." or an Asterisk (*) = Non-Toleranced Reference Dimension, shown for clarification purposes only. NOTE: All tolerances are Non-Cumulative.		PROPRIETARY INFORMATION This Engineering Drawing, and the information contained herein, is proprietary to Cole Hersee Company and may not be disclosed, re-produced, or in any other way transferred or communicated to any other party without the express written consent of an authorized representative of Cole Hersee Company.		Special Characteristics: ☒ CC Critical Characteristic, relating to Safety and/or Regulatory Compliance ☒ Significant Characteristic relating to Process Control ☒ KC Control Dimension relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer		 Cole Hersee Co. 20 Old Colony Ave., South Boston, MA, 02127 Phn: 617-268-2100 Web: www.colehersee.com			
Rev.	Description of Change	ECN No.	Date					SEE PAGE 1		FORM CHT-6 (2/07) Used On or Ref.: EX28646		Scale: 1:1	Drawn By: CN	Date Drawn: 09/14/09	Pg. 2 of 2	Description: SMART BATT ISO CTRL	
												Drawing / Part No.: 48540		Current Rev. D			

4

3

2

1