




PIN NUMBER	CIRCUIT	12VDC RESISTIVE LOAD
2	START	5 AMPS
3	ACCESSORY	10 AMPS
4 & 5	IGNITION	10 AMPS
1 & 6	BATTERY	

PINS 1 & 6 CONNECTED TOGETHER INTERNALLY  
PINS 4 & 5 CONNECTED TOGETHER INTERNALLY

- NOTES:
1. TOLERANCES PLUS OR MINUS 0.015 [0.38]
  2. ELECTRICAL CONTACT AREA SEALED TO IP67
  3. BACK OF SWITCH IS SEALED WHEN MATING CONNECTOR IS INSTALLED.
  4. FOR RESISTIVE LOAD RATING SEE CHART OR BACK OF SWITCH
  5. PIN LOCATIONS SEE CHART.
  6. SWITCH HOUSING: BLACK THERMOPLASTIC; STATIONARY CONTACTS: COPPER
  - SHAFT: ZINC DIE CAST; KNOB: BLACK PLASTIC WITH WHITE INDICATOR
  7. SWITCH TESTED TO SAE J259.
  8. SW. MUST NOT BREAK CIRCUIT OR BE DAMAGED IF TORQUED TO 15 IN-LBS [ 1.69Nm]

Revision Control Record				Rev.	Description of Change	ECN No.	Date	Tolerances Unless otherwise specifically noted, the following are default tolerances:			PROPRIETARY INFORMATION This Engineering Drawing, and the information contained herein, is proprietary to Cole Hersee Company and may not be disclosed, re-produced, or in any other way transferred or communicated to any other party without the express written consent of an authorized representative of Cole Hersee Company.	Special Characteristics:			Cole Hersee Co. 20 Old Colony Ave., South Boston, MA, 02127 Phn: 617-268-2100 Web: www.colehersee.com		
Rev.	Description of Change	ECN No.	Date					2-places +/- 0.02"	3-places +/- 0.005"	Angular +/- 1°		 Critical Characteristic, relating to Safety and/or Regulatory Compliance	 Significant Characteristic relating to Process Control	 Control Dimension relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer	Description: SW, ROT, 3POS, KNOB		
A	RELEASED DRAWING	12352	01/15/13												Drawing / Part No.: 95062-05		
															Current Rev. A		
								FORM CHT-6 (2/07)	Used On or Ref.: EX28803	Scale: 1:1			Drawn BY: A.VISCO	Date Drawn: 11/26/2012	Pg. 1 of 1		