
DSB30C30PB

30 V, 30 A Schottky Rectifier Diode

RoHS




Features

- Very low V_F
- Extremely low switching losses
- Low I_{RM} values
- Improved thermal behavior
- High reliability circuit operation
- Low voltage peaks for reduced protection circuits
- Low noise switching
- Terminals finish: 100% Pure Tin
- Epoxy meets UL 94V-0

Applications

- Rectifiers in Switch Mode Power Supplies (SMPS)
- Free wheeling diode in low voltage converters

Pinout Diagram (TO-220-3L AB)



C: Cathode; **A**: Anode; **tab**: Cathode

© 2025 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: TK.07/02/2025

Maximum Ratings (T_A = 25°C unless otherwise specified)

Symbol	Characteristics	Condition	Max.	Units
V_{RRM}	Peak Repetitive Reverse Voltage	–	30	V
V_{RWM}	Working Peak Reverse Voltage			
V_R	DC Blocking Voltage			
$I_{F(AV)}$	Average Rectified Forward Current	50% duty cycle @T_C=135°C, rectangular wave form	15(Per Leg)	A
			30 (Per Device)	
I_{FSM}	Peak One Cycle Non-Repetitive Surge Current (Per Leg)	10 ms, Half Sine pulse, T_J=25°C	340	A
P_{tot}	Total power dissipation	T_C= 25°C	70	W

Electrical Characteristics (T_A = 25°C unless otherwise specified)

Symbol	Characteristics	Conditions	Typ.	Max.	Units
V_{F1}	Forward Voltage Drop (Per Leg)[1]	@ 15A, Pulse, T_J = 25°C	–	0.55	V
V_{F2}		@ 15A, Pulse, T_J = 125°C	–	0.44	V
I_{R1}	Reverse Current (Per Leg)[1]	@V_R = rated V_R, T_J = 25°C	–	10	mA
I_{R2}		@V_R = rated V_R, T_J = 100°C	–	40	mA
C_T	Junction Capacitance (Per Leg)	@V_R = 5 V, T_C = 25 °C f_{SIG} = 1MHz	661	–	pF

Note 1: Pulse width < 300 µs, duty cycle < 2%

Thermal-Mechanical Specifications

Symbol	Characteristics	Condition	Specification	Units
T_J	Junction Temperature	–	-55 to +150	°C
T_O	Operation temperature	–	-55 to +125	°C
T_{stg}	Storage Temperature	–	-55 to +150	°C
M_D	Mounting torque	–	Min 0.4 Max 0.6	Nm
F_C	Mounting force with clip	–	Min 20 Max 60	N
R_{thJC}	Maximum Thermal Resistance Junction to Case	DC operation	1.75	°C/W
R_{thJH}	Typical Thermal Resistance Junction to Heat Sink	–	0.5	°C/W
wt	Approximate Weight	–	2	g

© 2025 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: TK.07/02/2025

Characteristic Curves

Fig. 1. Typical Forward Characteristics




Fig. 2. Typical Reverse Characteristics






Fig. 3. Typical Junction Capacitance




© 2025 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: TK.07/02/2025

Part Outline Drawing (TO-220-3L AB)



Symbol	Inches			Millimeters		
	Min.	Typical	Max.	Min.	Typical	Max.
A	0.140	–	0.190	3.56	–	4.83
A1	0.020	–	0.055	0.51	–	1.40
A2	0.080	–	0.115	2.03	–	2.92
b	0.015	–	0.040	0.38	–	1.02
b1	0.045	–	0.070	1.14	–	1.78
c	0.012	–	0.024	0.31	–	0.61
D	0.560	–	0.650	14.22	–	16.51
D1	0.330	–	0.371	8.38	–	9.42
E	0.380	–	0.420	9.65	–	10.67
e	–	0.100	–	–	2.54	–
e1	–	0.200	–	–	5.08	–
H1	0.230	–	0.270	5.84	–	6.86
L	0.500	–	0.580	12.70	–	14.73
L1	–	–	0.250	–	–	6.35
ØP	–	0.140	–	–	3.56	–
Q	0.100	–	0.135	2.54	–	3.43

Part Number and Marking




D = Diode
S = Schottky Diode
B = Ultra Low VF
30 = Current Rate (30A)
C = Common Cathode
30 = Voltage Rating (30V)
PB = Package Code (TO-220AB)
YY = Year
WW = Work Week
S = Plant Location Code
XXXXXXXXX = Lot Number

Ordering Information

Part Number	Marking	Packing Mode	Quantity
DSB30C30PB	DSB30C30PB	Tube	50 pcs/ tube

Packing Specifications



Disclaimer Notice

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications.
Read complete Disclaimer Notice at http://www.littelfuse.com/disclaimer-electronics.

IXYS Part of: Littelfuse

© 2025 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: TK.07/02/2025