


KSC9 Series

Sealed Tactile Switch for SMT 6.2 x 6.2 mm, with 7.7 mm Height Hard Actuator



Specifications

Function	Momentary action
Contact Arrangement	1 make contact = SPST, N.O.
Terminals	J bend & Gullwing type for SMT
Sealing	IP67
Packaging	Switches delivered on continuous tape & reels of 950 pieces Dimensions according to EIA RS-481/ IEC 60286-3 standard External diameter 380 ± 2 mm

Description

The KSC9 series of sealed tactile switches for SMT are IP67 rated, 7.7 mm high momentary action tactile switches, featuring a hard actuator compatible with button. The switches are available with a variety of operating forces depending on model and have a lifespan of 300,000 cycles.

The KSC9 series are designed to give users a positive adaptable tactile feeling, perfect for industrial electronics and consumer, automotive and instrumentation applications


Features & Benefits

- Positive adaptable tactile feeling
- Hard actuator 7.7mm high
- IP67
- Compatible with lead free reflow soldering process of SMT devices
- RoHS and REACH compliant


Applications

- Industrial electronics
- Instrumentation
- Transportation
- Consumer

Dimensions (mm) J Termination



Dimensions (mm) G Termination



KSC9 Series


Sealed Tactile Switch for SMT 6.2 x 6.2 mm, with 7.7 mm Height Hard Actuator



Mechanical Characteristics

Part #	Operating Force FA (Newtons)	Operating Life (operations)	Travel (mm)
KSC921	1.7 ± 0.5	300,000	0.4 ± 0.2
KSC931	2.55 ± 0.65	300,000	0.4 ± 0.2
KSC941	3.4 ± 0.85	300,000	0.4 ± 0.2

Soldering Profile




Note: Up to 2 reflow cycles in accordance with the above temperature profile


Soldering process: Depending on the application, this component is suited to the following methods:

- Terminals being silver or gold plated over a nickel barrier, the use of slightly activated flux is suitable.
- Lead free soldering process in accordance with the definition on the left.

J Terminations (mm)



G Terminations (mm)




KSC9 Series

Sealed Tactile Switch for SMT 6.2 x 6.2 mm, with 7.7 mm Height Hard Actuator



Tape & Reel

Reeling Direction
Out of Production



See Detail R

Detail R
Scale 1

Scale 0.25

Packaging Details

Type	Tape & reel
Number of Parts in Packaging	950
Other Information	Tape and reel per EIA 481
Transport Conditions	According to specification NF H00-060

Ordering Number

Our easy build-a-switch concept allows you to mix and match options to create the switch you need. To order, select desired option from each category and place it in the appropriate box. For any part number different from those listed below, please consult your local representative.

KSC9 - x - x - x - xxx

Operating Force

- 2: 1.7 N (170 grams)
- 2: 2.55 N (255 grams)
- 4: 3.4 N (340 grams)

Contact Material

- 1: Silver
- 3: Gold

LFS Lead free compatible, silver plated

LFG Lead free compatible, gold plated

Termination

- J: J Bend
- G: Gullwing




BTN - KSC9 - x - x

Type

None: 15.4mm height mounted

Color

- 20: Light grey
- 40: Red
- 80: White
- 90: Black



SWITCH WITH CAP

Liability Limitation

This datasheet does not provide enough information for applications that require a certain level of quality or safety such as automotive, medical systems, or safety equipment. Please contact customer service for the contractual specification package.

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at <http://www.littelfuse.com/disclaimer-electronics>.