

JCASE® Series

Cartridge Fuses – Rated 32V



Description

The JCASE™ is a cartridge style fuse with female terminal design, providing both increased time delay and low voltage drop to protect high current circuits and handle inrush currents.

Features & Benefits

- Semitransparent cover makes it easier to see when fuse blows
- High-contrast amperage stamp on the top of the housing aids identification
- Color coding indicates amperage rating for each fuse
- Comply with ISO 8820-4
- SHUNT version available

Applications

- Cars / SUVs
- Trucks
- Offroad vehicles
- Buses
- Watercraft as approved by Littelfuse®

Agency Approvals

Agency	Agency File Number	Current Rating (A)
	20130624-E71611	20 - 60

[See Disclaimer Notice](#)

Specifications

Voltage Rating:	32 V DC
Interrupting Rating:	1000 A @ 32 V DC
Recommended Environmental Temperature:	-40 °C to +125 °C
Housing Material:	PA66-GF13 (UL 94 Flammability rating – HB)
Cover Material:	PC (UL 94 Flammability rating – HB)
Typical Weight per Fuse:	3.8 g
Fuse Insertion Force:	53 N Max. (12 lb.)
Extraction Force:	9 N Min (2 lb.)
Comply With:	SAE 2741, ISO 8820-4

Additional Information



Resources



Samples








Ordering Information

Part Number	Current Rating (A)	Package Size
0495xxx.ZXA	20 – 60	2200
0495xxx.UXA	20 – 60	500
0495xxx.TXA	20 – 60	10
0495900.Z	SHUNT	2200
0495900.X	SHUNT	1

JCASE® Series


Cartridge Fuses – Rated 32V

Ratings


Part Number	Current Rating (A)	Housing Material Color	Test Cable Size (mm ²)	Typ. Voltage Drop (mV)	Typ. Cold Resistance (mΩ)	Typ. I ² t (A ² s)
0495020_	20		4	106	4.29	1700
0495025_	25		4	101	3.28	3200
0495030_	30		4	91	2.12	1500
0495040_	40		4	87	1.30	3700
0495050_	50		6	88	0.99	8800
0495060_	60		6	87	0.76	19 500
0495900_	SHUNT		-	-	-	-

Dimensions

Dimensions in mm. Please refer to the outline drawing for dimensions and tolerances.




RECOMMENDED MATING CAVITY



JCASE® Series

Cartridge Fuses – Rated 32V

Time-Current Characteristic



% of Rating	Opening Time Min. / Max. (s)
110	360 000 / -
135	60 / 1800
200	4 / 60
350	0.2 / 7
600	0.04 / 1

- 20 A
- 25 A
- 30 A
- 40 A
- 50 A
- 60 A


Note: Current recommendation may be impacted by the final condition of the application (terminals characteristics, wire size etc.). Please contact Littelfuse® for more information.

Typical Derating Curves

Temperature security margin is 20%.

Wire Cross Section And Fixture Test Set Up Refer To ISO 8820-4

Please contact Littelfuse® for Details Regarding Derating Test Set Up.



	Max. allowed current load (A) at ambient temperature based on typical derating						
	-40 °C	0 °C	20 °C	65 °C	85 °C	110 °C	125 °C
20 A	20	20	20	17	15	12	10
25 A	25	25	25	20	18	15	13
30 A	30	30	30	28	25	21	18
40 A	40	40	40	37	33	27	23
50 A	50	50	49	40	36	29	25
60 A	60	60	60	51	46	38	33

- 20 A
- 25 A
- 30 A
- 40 A
- 50 A
- 60 A

Note: Current recommendation may be impacted by the final condition of the application (terminals characteristics, wire size etc.). Please contact Littelfuse® for more information.

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at <https://www.littelfuse.com/legal/disclaimers/product-disclaimer.aspx>