HiPerFRED

V_{RRM}	=	200 V
I_{FAV}	=	60 A
t_{rr}	=	45 ns

High Performance Fast Recovery Diode
Low Loss and Soft Recovery
Single Diode

Part number

DPF60I200HA



Backside: cathode

Features / Advantages:

- Planar passivated chips
- Very low leakage current
- Very short recovery time
- Improved thermal behaviour
- Very low Irm-values
- Very soft recovery behaviour
- Avalanche voltage rated for reliable operation
- Soft reverse recovery for low EMI/RFI
- Low Irm reduces:
  - Power dissipation within the diode
  - Turn-on loss in the commutating switch

Applications:

- Antiparallel diode for high frequency switching devices
- Antisaturation diode
- Snubber diode
- Free wheeling diode
- Rectifiers in switch mode power supplies (SMPS)
- Uninterruptible power supplies (UPS)

Package: TO-247

- Industry standard outline
- RoHS compliant
- Epoxy meets UL 94V-0

Disclaimer Notice

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.

© 2022 IXYS all rights reserved

Fast Diode

Symbol	Definition	Conditions		Ratings min.	typ.	max.	Unit
V_{RSM}	*max. non-repetitive reverse blocking voltage*		T_{VJ} = 25°C			200	V
V_{RRM}	*max. repetitive reverse blocking voltage*		T_{VJ} = 25°C			200	V
I_R	*reverse current, drain current*	V_R = 200 V	T_{VJ} = 25°C			1	µA
		V_R = 200 V	T_{VJ} = 150°C			0,2	mA
V_F	*forward voltage drop*	I_F = 60 A	T_{VJ} = 25°C			1,17	V
		I_F = 120 A				1,41	V
		I_F = 60 A	T_{VJ} = 150°C			0,99	V
		I_F = 120 A				1,27	V
I_{FAV}	*average forward current*	T_C = 135°C rectangular d = 0.5	T_{VJ} = 175°C			60	A
V_{F0}	*threshold voltage* } *for power loss calculation only*		T_{VJ} = 175°C			0,68	V
r_F	*slope resistance*					4,6	mΩ
R_{thJC}	*thermal resistance junction to case*					0,55	K/W
R_{thCH}	*thermal resistance case to heatsink*				0,25		K/W
P_{tot}	*total power dissipation*		T_C = 25°C			275	W
I_{FSM}	*max. forward surge current*	t = 10 ms; (50 Hz), sine; V_R = 0 V	T_{VJ} = 45°C			550	A
C_J	*junction capacitance*	V_R = 100 V f = 1 MHz	T_{VJ} = 25°C		108		pF
I_{RM}	*max. reverse recovery current*	I_F = 60 A; V_R = 100 V $-di_F/dt$ = 200 A/µs	T_{VJ} = 25 °C		4		A
			T_{VJ} = 125 °C		10		A
t_{rr}	*reverse recovery time*		T_{VJ} = 25 °C		45		ns
			T_{VJ} = 125 °C		70		ns

OBSOLETE

© 2022 IXYS all rights reserved

Package TO-247			Ratings			
Symbol	**Definition**	**Conditions**	**min.**	**typ.**	**max.**	**Unit**
I_{RMS}	*RMS current*	per terminal			70	A
T_{VJ}	*virtual junction temperature*		-55		175	°C
T_{op}	*operation temperature*		-55		150	°C
T_{stg}	*storage temperature*		-55		150	°C
Weight				6		g
M_D	*mounting torque*		0,8		1,2	Nm
F_C	*mounting force with clip*		20		120	N

Product Marking



Part description

D = Diode
P = HiPerFRED
F = ultra fast
60 = Current Rating [A]
I = Single Diode
200 = Reverse Voltage [V]
HA = TO-247AD (2)

Ordering	Ordering Number	Marking on Product	Delivery Mode	Quantity	Code No.
Standard	DPF60I200HA	DPF60I200HA	Tube	30	515324

Equivalent Circuits for Simulation

** on die level* $T_{VJ} = 175°C$



		Fast Diode	
$V_{0\,max}$	*threshold voltage*	0,68	V
$R_{0\,max}$	*slope resistance **	2	mΩ

© 2022 IXYS all rights reserved

Outlines TO-247



Sym.	Inches min.	Inches max.	Millimeter min.	Millimeter max.
A	0.185	0.209	4.70	5.30
A1	0.087	0.102	2.21	2.59
A2	0.059	0.098	1.50	2.49
D	0.819	0.845	20.79	21.45
E	0.610	0.640	15.48	16.24
E2	0.170	0.216	4.31	5.48
e	0.430 BSC		10.92 BSC	
L	0.780	0.800	19.80	20.30
L1	-	0.177	-	4.49
Ø P	0.140	0.144	3.55	3.65
Q	0.212	0.244	5.38	6.19
S	0.242 BSC		6.14 BSC	
b	0.039	0.055	0.99	1.40
b2	0.065	0.094	1.65	2.39
b4	0.102	0.135	2.59	3.43
c	0.015	0.035	0.38	0.89
D1	0.515	-	13.07	-
D2	0.020	0.053	0.51	1.35
E1	0.530	-	13.45	-
Ø P1	-	0.29	-	7.39

OBSOLETE



© 2022 IXYS all rights reserved

Fast Diode



Fig. 1 Forward current I_F versus V_F



Fig. 2 Typ. reverse recov. charge Q_{rr} versus $-di_F/dt$



Fig. 3 Typ. reverse recov. current I_{RM} versus $-di_F/dt$



Fig. 4 Typ. dynamic parameters Q_{rr}, I_{RM} versus T_{VJ}



Fig. 5 Typ. reverse recov. time t_{rr} versus $-di_F/dt$



Fig. 6 Typ. forward recovery voltage V_{FR} & time t_{fr} versus di_F/dt



Fig. 7 Typ. recovery energy E_{rec} versus $-di_F/dt$



R_{thi} [K/W]	t_i [s]
0.0800	0.0010
0.1400	0.0050
0.1500	0.0450
0.1800	0.2450

Fig. 8 Transient thermal impedance junction to case

OBSOLETE

© 2022 IXYS all rights reserved