


 18.00 ± 0.02 [0.71 ± 0.001]

0

0

81.00 MAX

[3.189]



SPECIFICATIONS:

VOLTAGE RATING: 600VAC/DC

AMPERE RATING: 30 AMPERES

INTERRUPT RATING: 100kA

TERMINAL TYPE: 1/4" QUICK CONNECT

APPROVALS: UL RECOGNIZED (E14721)

CSA CERTIFIED (LR7316)

CCC APPROVED (2010010308391538)

| 1 | | | | | | |
|--|---------|--|--|--------------|----------------|-----|
| NO | COMPONE | ON TV | DES | CRIPTION | QTY/M | U/M |
| BILL OF MATERIAL | | | | | | |
| <s></s> | | CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE | | | | |
| • | | DENOTES CRITICAL CHARACTERISTICS. | | | | |
| СРК | | DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE | | | | |
| (হা) | | DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS. | | | | |
| CP MI | | MUST SHOV | DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE. | | | |
| MATL SPEC | | | | FINISH | | |
| DRW JMOLER | | | DATE 9/26/2022 | SCALE NTS | FINISH GOOD WT | |
| | | 0/20/2022 | 8/26/2022 | | GRAMS/PIECE | |
| UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN | | | | | | |

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN BRACKETS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994

3RD ANGLE PROJECTION

TITLE

LPSM001QCID OUTLINE



DRWG

OL-LPSM001QCID