

	REVISION							
REV	DATE	DESCRIPTION						
Α	9/2/22	525636GCP - RELEASE MRY						
В	11/3/22	525897ECP/D - ADD DEPTH DIMENSION MRY						
С	2/13/25	528562ECP/D - CHANGE WIDTH TOLERANCE MRY						

SPECIFICATIONS:

VOLTAGE RATING: 600VAC/DC

AMPERE RATING: 30 AMPERES

INTERRUPT RATING: 100kA

TERMINAL TYPE: 1/4" QUICK CONNECT

APPROVALS: UL RECOGNIZED (E14721)

CSA CERTIFIED (LR7316) CCC APPROVED (2010010308391538)

1									
NO	COMPONE	ON TV	DESCRIPTION		QTY/M	U/M			
BILL OF MATERIAL									
<s> C</s>		CRIT!	CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE						
•		DENOTES CRITICAL CHARACTERISTICS.							
СРК [DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE							
<u>(ST)</u>		DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.							
CP MU SH		MUST SHOV	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.						
MATL SPEC				FINISH					
DRW JMOLER			DATE 8/26/2022	SCALE NTS	FINISH GOOD WT GRAMS/PIECE				
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN									

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN
BRACKETS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING
TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994

3RD ANGLE PROJECTION

TITLE

LPSM003QCID OUTLINE



C

OL-LPSM003QCID