

# Fuses for Photovoltaic Systems

**COMPANY****E339112****LITTELFUSE INC**

6133 N. River Rd, Suite 500  
Rosemont, IL 60018 United States

*View model for additional information*

Model(s): [KLKD-CN](#) followed by 15-30 (ampere rating), may be followed by -R.

Model(s): [KLKDX](#), where *x* is replaced with 0.1-30 (ampere rating), may be followed by -R

**Nonrenewable Fuses**, Model(s): [SPFJ 250-400](#), [SPFJ 450](#), [SPFJ 70 - 200](#)

**Nonrenewable Fuses**, Model(s): [SPF-E x](#), where *x* is replaced with 25-30A (ampere rating), followed by R, may be followed by SN

**Nonrenewable Fuses**, Model(s): [SPFJxxxL](#) where XXX is replaced with 125-200

**Nonrenewable Fuses**, Model(s): [SPFx](#), where *x* is replaced with 1-30A (ampere rating), may be followed by R, may be followed by SN

**Nonrenewable Fuses**, Model(s): [SPFx](#), where *x* is replaced with 1-30A (ampere rating), may be followed by R, may be followed by SN. Followed by CN

**Nonrenewable Fuses**, Model(s): [SPFx](#), where *x* is replaced with 1-30A (ampere rating), may be followed by RT, may be followed by SN, followed by CN

**Nonrenewable Fuses**, Model(s): [SPFx](#), where *x* is replaced with 25-30A (ampere rating), followed by -E, may be followed by -R, may be followed by -SN Followed by CN

**Nonrenewable Fuses**, Model(s): [SPFx](#), where *x* is replaced with 25-30A (ampere rating), may be followed by R, may be followed by SN Followed by CN

**Nonrenewable Fuses**, Model(s): [SPFx](#), where *x* is replaced with 25-30A (ampere rating), may be followed by RTE, may be followed by SN, followed by CN

**Nonrenewable Fuses**, Model(s): [SPFx](#), where *x* is replaced with 25A-30A (ampere rating), may be followed by R, may be followed by SN

**Nonrenewable Fuses**, Model(s): [SPXCxxx](#), where XXX is replaced with 1-4A (ampere rating), may be followed by SN, may be followed by R

**Nonrenewable Fuses**, Model(s): [SPXVxx](#), where XX is replaced with 01-20A (ampere rating), may be followed by SN followed by CN

**Nonrenewable Fuses**, Model(s): [SPXVxx](#), where XX is replaced with 1-60A (ampere rating), may be followed by SN

**Nonrenewable Fuses**, Model(s): *SPXVxx, where XX is replaced with 25-32A (ampere rating), may be followed by SN followed by M,*

**Nonrenewable Fuses**, Model(s): *SPXVxx, where XX is replaced with 25-60A (ampere rating), may be followed by SN, followed by M,*

**Nonrenewable Fuses**, Model(s): *SPXVxx, where XX is replaced with 35-60A (ampere rating), may be followed by SN*

Last Updated on 2026-04-07

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."