



| REVISION | | |
|----------|---------|--------------------------------------|
| REV | DATE | DESCRIPTION |
| A | 9/10/19 | 521205GCP - RELEASE MRY |
| B | 11/2/22 | 525830ECP/D - ADD LABEL LOCATION MRY |

| | |
|-----|--|
| <S> | CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE |
| ● | DENOTES CRITICAL CHARACTERISTICS. |
| CPK | DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE |
| ST | DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS. |
| CP | DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE. |

A

| | | | |
|--------------|-------------------|--------------|-------------------------------|
| MATL SPEC | | FINISH | |
| DRW myork | DATE 8/12/2019 | SCALE NTS | FINISH GOOD WT GRAMS/PIECE |

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN BRACKETS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994

3RD ANGLE
PROJECTION



TITLE SPXV-M SERIES OUTLINE



| REVISION | DRWG NO. | SHEET 1 OF 1 |
|----------|-------------|--------------|
| B | OL-SPXV000M | |