




- NOTES:
- 1. RATING: CONTINUOUS -175 AMP 6-12
24-36 VOLTS DE, INTERMITTENT - 1000 AMPS
6-12-24-36 VOLTS DC, 15 SEC "ON" 5 MIN "OFF"
 - 2. ALL STEEL PARTS PLATED
 - 3. HARDWARE ASSEMBLED
 - 4. ALL DIMENSIONS REFERENCE ONLY

Revision Control Record				Rev.	Description of Change	ECN No.	Date	Tolerances Unless otherwise specifically noted, the following are default tolerances:			PROPRIETARY INFORMATION		Special Characteristics:		Cole Hersee Co.	
Rev.	Description of Change	ECN No.	Date					2-places +/- 0.02"	3-places +/- 0.005"	Angular +/- 1°	This Engineering Drawing, and the Information contained herein, is proprietary to Cole Hersee Company and may not be disclosed, re-produced, or in any other way transferred or communicated to any other party without the express written consent of an authorized representative of Cole Hersee Company.	CC Critical Characteristic, relating to Safety and/or Regulatory Compliance	X Significant Characteristic relating to Process Control	KC Control Dimension relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer	20 Old Colony Ave., South Boston, MA, 02127 Phn: 617-268-2100 Web: www.colehersee.com	
AA	CHANGE NOTE 3	09252	04/16/09												Description:	
AB	ADDED "X" TO STUD TOPS	09563	12/7/09												SWITCH, MASTER DISCONNECT	
															Drawing / Part No.:	Current Rev.
								FORM CHT-6 (2/07)	Used On or Ref.:		Scale: 1:1	Drawn BY: VAK	Date Drawn: 10/19/54	Pg. 1 of 1	M-284	AB