

THIS DRAWING AND THE INFORMATION CONTAINED WITHIN IT ARE CONFIDENTIAL AND MAY NOT BE COPIED OR DISCLOSED WITHOUT THE WRITTEN PERMISSION OF LITTELFUSE.

REVISIONS			
REV.	DESCRIPTION	DATE	DESIGNED / APPROVED
A	FIRST ISSUE FOR OUTLINE DRAWING	09-July-2020	Gasparini / Tinto





(Z)


DETTAGLIO A
SCALA 2 : 1



Box PA 6.6
CTI 300








Protection PA 6
CTI 3000


Cover BMC 9/20
CTI 600

Connector PBT
CTI 400



A

Spare part 00226200
Protection open 70 mmq



(*)

ELECTRICAL CHARACTERISTICS

- Nominal operating voltage: 12 ÷ 24 V
- Max continuos current on contacts: 250 A at 23°C
- Max current short duration on contacts: 2000 A at 23°C for 30 sec.

PRECSRIPTIONS

- (Z): Self-sticking immovable label size 48x23 mm with: white background, Polyester material with thickness 0.006-0.01 mm, printed by thermic printer.
Good quality of adhesive support it cannot damage the application surface, resistant to abrasive action, resistant to environment agents and UV rays, self burn out, resistant to humidity and to oils and greases used on the automotive line.
- test the device according to Littelfuse CPP 00027
- Torque of screws M10=20 Nm max
- Fix the device by M8 screws UNI 5931:1984 and washers 8.4x1.7 UNI 6592:1969
- (*): Production date
- The distance between the contacts must be 2 mm minimum

SAP drawing number:

Material and treatments:

DIMENSIONS AND TOLERANCES IN MILLIMETERS, DEFINED ACCORDING TO ISO 1101-2017.

linear dimensions

0,5 3	>3 6	>6 30	>30 120	>120 400	>400 1000	>1000 2000
±0,2	±0,3	±0,5	±0,8	±1,2	±2	±3

angle (for range of lengths)

up to 10	>10 50	>50 120	>120 400
±1°30'	±1°	±0°30'	±0°15'

●	FIT/ FUNCTION CRITICAL CHARACTERISTICS SYMBOL
<S>	SAFETY/ COMPLIANCE CRITICAL CHARACTERISTICS SYMBOL
CPK	DENOTES CPK DIMENSIONS MINIMUM CPK VALUE
(ST)	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE.PROCEDURE FOR MEASUREMENTAND TRACKINGTO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS
CP	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE

	NAME	DATE
DRAWN	L. Dal Molin	28/05/2019
CHECKED	-	-
	-	-
	-	-

Littelfuse
Expertise Applied | Answers Delivered

FORM NO. CVP-PE40-00013 REV.A
FIRST ANGLE PROJECTION

TITLE
GENERAL ELECTRICAL MAIN SWITCH
TGC/RMCDE 24V SEP (+E-) 2P

SIZE A1 | DWG. NO. OL-08097463 | REV. A

DO NOT SCALE DRAWING | SCALE 1:1 | SHEET 1 OF 1