



**SPECIFICATIONS:** 

**VOLTAGE RATING:** 600V

AMPERE RATING: 60 AMPERES
INTERRUPT RATING: 200kA
TERMINAL TYPE: BOX LUG

**SUGGESTED TORQUE:** 2.8 N-m (25 IN-LBS) 6-14 AWG 5.6 N-m (50 IN-LBS) 2-4 AWG

MG Cu/Al

**WIRE RANGE**: 2 -14 AWG Cu/Al SOLID/STRANDED

**APPROVALS:** UL LISTED (FILE NO. E14721) CSA CERTIFIED (FILE NO. LR7316)

•	DENOTES CRITICAL CHARACTERISTICS.						
CPK	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE						
<u>(ST)</u>	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.						
СР	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.						
MATL SPEC	FIN	FINISH					
DRW MYORK		DATE 3/21/2011		SCALE NTS		FINISH GOOD WT  GRAMS/PIECE	
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN BRACKETS [ ] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994							
3RD ANGLE PROJECTION							
TITLE LFJ60060 SERIES OUTLINE							
Littelfuse® DES PLAINES, ILLINOIS 60016			REVISI	ON	DRWG NO.	SHEET	1 OF 1
			С		OL-LFJ6	DL-LFJ60060	