



- NOTES:**
1. TOLERANCES PLUS OR MINUS 0.015 [0.38]
 2. CONTACT AREA SEALED TO IP67
 3. BACK OF SWITCH SEALED WHEN MATING CONNECTOR IS INSTALLED
 4. FOR RESISTIVE LOAD RATING SEE CHART OR BACK OF SWITCH
 5. KEY REMOVEABLE IN OFF POSITION ONLY
 6. PIN LOCATIONS SEE CHART
 7. MATERIALS: HOUSING BLACK THERMOPLASTIC
INTERNAL STATIONARY CONTACTS COPPER
 8. START LOCKOUT FEATURE. SWITCH MUST GO TO "OFF" POSITION BEFORE THE START CIRCUIT CAN BE RE-ENERGIZED
 9. KEY BOOT FITS OVER FACE NUT
 10. SWITCH TESTED TO SAE J259, UL RECOGNIZED TO UL 1054
 11. SWITCH SUPPLIED WITH SINGLE KEY CODE 601
 12. SWITCH SAME AS 95060-01 EXCEPT SINGLE KEY CODE
 13. SW. MUST NOT BREAK CIRCUIT OR BE DAMAGED IF TORQUED TO 15 IN-LBS [1.69Nm]
 14. IF THE APPLICATION MOUNTS THE SWITCH WITH THE LOCK CYLINDER OR LEVER APPROACHING VERTICAL, CONTACT THE FACTORY FOR AN APPLICATION REVIEW AND POTENTIAL ALTERNATE PRODUCTS BEFORE DESIGN IS SET.

Revision Control Record				Tolerances Unless otherwise specifically noted, the following are default tolerances: • 2-place Decimal Dimensions +/- .02" • 3-place Decimal Dimensions +/- .005" • Angular Dimensions +/- 1.0 Deg. • Metric: Refer to equivalent English Dimension Tolerance >>> NOTE: All tolerances are Non-Cumulative. <<<	PROPRIETARY INFORMATION This Engineering Drawing, and the information contained herein, is proprietary to Cole Hersee Company and may not be disclosed, re-produced, or in any other way transferred or communicated to any other party without the express written consent of an authorized representative of Cole Hersee Company.	Special Characteristics: CC Critical Characteristic, relating to Safety and/or Regulatory Compliance X Significant Characteristic relating to Process Control (SPC) KC Control Dimension relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer (Note that the identification of any Characteristics as being "Special" does not alter the requirement that ALL specified dimensions & tolerances must be met.)	Cole Hersee Co.	
Rev.	Description of Change	ECN No.	Date				Dimensional Units All dimensions are expressed in inches except those shown in brackets (xxx) are expressed in millimeters	DESIGN CONTROL It is the responsibility of the individual using / referencing this drawing to assure that the noted design revision level agrees with the revision level of the Controlled Document (Master Drawing). This is a NON-CONTROLLED DOCUMENT unless otherwise specifically noted.
D	ADDED HENCOL 13; ADDED TORQUE NOTE	13171	6/17/13	"REF." or an Asterisk (*) = Non-Toleranced Reference Dimension, shown for clarification purposes only.	Drawn By: DPS	Date Drawn: 9/19/07	Description: SW, ROT, 4POS, PLSTC Drawing / Part No.: 95060-24 Current Rev.: D	
C	ADDED MADE IN TAIWAN	11215	7/15/11	Used On 95060-01 or Ref.:	Scale: 1:1	Responsible Engineer: JT		
B	ADDED CHART & UL	10254	6/24/10			PAGE 1 Created using Autocad Inventor		
A	RELEASED DRAWING	07397	9/19/07					