



$\varnothing 1.52$
 $[\varnothing 0.060]$

$\varnothing 10.31 \pm 0.10$
 $[\varnothing 0.406 \pm 0.004]$



7.11 ± 0.51
 $[0.280 \pm 0.020]$

FULL PIN EXTENSION WHEN FUSE IS OPEN



38.09 ± 0.79
 $[1.500 \pm 0.031]$

REVISION		
REV	DATE	DESCRIPTION
A	6/28/22	525364GCP - RELEASE MRY

APPROXIMATE SHIPPING WEIGHT: 10 FUSES / .12 LB.

1					
NO	COMPONENT NO	DESCRIPTION			QTY/M
BILL OF MATERIAL					
<S>	CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE				
●	DENOTES CRITICAL CHARACTERISTICS.				
CPK	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE				
ST	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.				
CP	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.				
MATL SPEC			FINISH		
DRW Jeff Moler		DATE 6/14/2022		SCALE NTS	FINISH GOOD WT GRAMS/PIECE
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN BRACKETS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994					
3RD ANGLE PROJECTION					
TITLE FLA 1/10 - 10A OUTLINE					
Littelfuse® CHICAGO, ILLINOIS 60631			REVISION A	DRWG NO. OL-0FLA010	SHEET 1 OF 1

A