

 49.5 ± 0.50 $[1.95 \pm 0.020]$

REVISION

DESCRIPTION

520502GCP - RELEASE MRY

DATE

3/21/19

SPECIFICATIONS:

VOLTAGE RATING: 600V

AMPERE RATING: 60 AMPERES

INTERRUPT RATING: 200kA TERMINAL TYPE: BOX LUG

SUGGESTED TORQUE: 2.8 N-m (25 IN-LBS) 6-14AWG

5.6 N-m (50 IN-LBS) 2-4 AWG

WIRE RANGE: 2-14 AWG Cu/Al SOLID/STRANDED

APPROVALS: UL LISTED (FILE NO. E14721) CSA CERTIFIED (FILE NO. 007316_0_000)

•	DENOTES CRITICAL CHARACTERISTICS.			
СРК	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE			
(ST)	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.			
СР	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.			
MATL SPEC			FINISH	
DRW DATE MYORK 3/4/2019			SCALE NTS	FINISH GOOD WT GRAMS/PIECE
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN				

CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE.

BRACKETS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING
TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994

3RD ANGLE PROJECTION $\oplus \Box$

<S>

TITLE

LFC60060C-HX SERIES OUTLINE



DRWG NO.

SHEET 1 OF 1 SERIES OL-LFC60060C-HX