

24.0 [.94]

CE



REV									
A	8/26/22			52561	L4GCP -	RELEASE MRY			
	1								
Ν	IO COMPONE	NT NO			RIPTIO			QTY/M	U/M
BILL OF MATERIAL									
<s> CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE</s>									
	•	DENOTES CRITICAL CHARACTERISTICS.							
СРК		DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE							
		DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION							
(ST)		OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN							
		LITTELFUSE INSPECTION INSTRUCTIONS.							
		DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS							
СР		SHOWN ON DRAWING AND INITIALLY LOCATED TO							
MATL SPEC		ALLO\	W FOR MAXIMUM						Ч
I M	ALL SPEC				FINISH	I			
DF	RW		DATE	+	SCALE		F	NISH GOOD V	VT
JMOLER			8/22/2022				GRAMS/PIECE		
Γ		RWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN							
BRACKETS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCI TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994									ANCING
3RD ANGLE									
PROJECTION									
TITLE 3PH12P18MM OUTLINE									
			JEIHZEI	LOUIN	1001				
			R	REV	ISION	DRWG NO.		CHEET	1 OF 1
	// Lit	tel	tuse						
	CHICAG	O, ILLIN	OIS 60631		A	OL-3PH	12	2P18M	чΙ

REVISION