CAD GENERATED DRAWING - NO PENCIL CHANGES ALLOWED

PART NO.
GDB63101Z

NOTES:

1. AGENCY INFORMATION:
   UL FILE NO. E309688
2. MATERIALS:
   INSULATOR-THERMOPLASTIC
   CONNECTOR-BRASS
3. TERMINATION:
   LINE: 3/0-350MCM
   LOAD: (2) 2-14 AWG
   (5) 6-14 AWG
   (4) 8-14 AWG
4. RATINGS:
   600V
   MAXIMUM AMP PER POLE-310A
5. TORQUE:
   LINE: 230 IN-LB
   LOAD: 2-14AWG 31 IN-LB
   6-14 AWG 18 IN-LB
   8-14 AWG 18 IN-LB



NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M

BILL OF MATERIAL

MATL SPEC	FINISH			
	NONE			
DRW M YORK	DATE 4/9/18	SCALE		
CHK	DATE	SUPER DRW		
APPD	DATE	RAW STK WT		LBS/M

COPIES TO: 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 23 33 43 53

TITLE: GDB6310 SERIES DISTRIBUTION BLOCK OUTLINE

Littelfuse® CHICAGO, ILLINOIS 60631

DRWG. NO. DL-GDB6310

REVISION A

LTR	REVISION	CHK	APD
A	519180GCP - RELEASE 4/17/18 MRY		

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

● DENOTES CRITICAL CHARACTERISTICS.

CPK DENOTES CPK DIMENSIONS,-MINIMUM CPK VALUE

(ST) DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.

CP DENOTES CP DIMENSIONS,-MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.