

4

3

2

1

B

B

A

A

48610-01	12.1	13.0	24.2	26.0	18.0	7.0	34.0	16.0	10	60	1	15	15	12805
48610	12.1	13.0	24.2	26.0	18.0	7.0	34.0	16.0	10	60	1	15	15	NONE
COLE HERSEE PART NUMBER	12V System Discharge Threshold	12V System Charge Threshold	24V System Discharge Threshold	24V System Charge Threshold	12V System Over-Voltage Threshold	12V System Under-Voltage Threshold	24V System Over-Voltage Threshold	24V System Under-Voltage Threshold	Charge Time Delay (seconds)	Discharge Time Delay (seconds)	Alarm Timeout Delay (minutes)	Manual Override Timeout (minutes)	Alarm Override Timeout (minutes)	KIT

Revision Control Record

Rev.	Description of Change	ECN No.	Date
SEE PAGE 1			

Tolerances Unless otherwise specifically noted, the following are default tolerances:
2-places 3-places Angular
 +/- 0.02" +/- 0.005" +/- 1'
 Metric: Shown in [] refers to equivalent English Dim Tol
 "REF." or an Asterisk (*) = Non-Toleranced Reference Dimension, shown for clarification purposes only.
 NOTE: All tolerances are Non-Cumulative.

PROPRIETARY INFORMATION This Engineering Drawing, and the information contained herein, is proprietary to Cole Hersee Company and may not be disclosed, re-produced, or in any other way transferred or communicated to any other party without the express written consent of an authorized representative of Cole Hersee Company.

Special Characteristics:
 Critical Characteristic, relating to Safety and/or Regulatory Compliance
 Significant Characteristic relating to Process Control
 Control Dimension relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer

Cole Hersee Co.
 20 Old Colony Ave., South Boston, MA, 02127
 Phn: 617-268-2100 Web: www.colehersee.com

Description:
LVD,MINI,10A

Drawing / Part No.: 48610 **Current Rev.:** G

FORM CHT-6 (2/07) Used On or Ref.: EX28439A Scale: 1:1 Drawn By: CN Date Drawn: 03/18/09 Pg. 2 of 2