

4

3

2

1

B

B

A

A

48610-01	12.1	13.0	24.2	26.0	18.0	7.0	34.0	16.0	10	60	1	15	15	12805
48610	12.1	13.0	24.2	26.0	18.0	7.0	34.0	16.0	10	60	1	15	15	NONE
COLE HERSEE PART NUMBER	12V System Discharge Threshold	12V System Charge Threshold	24V System Discharge Threshold	24V System Charge Threshold	12V System Over-Voltage Threshold	12V System Under-Voltage Threshold	24V System Over-Voltage Threshold	24V System Under-Voltage Threshold	Charge Time Delay (seconds)	Discharge Time Delay (seconds)	Alarm Timeout Delay (minutes)	Manual Override Timeout (minutes)	Alarm Override Timeout (minutes)	KIT

**Revision Control Record**

Rev.	Description of Change	ECN No.	Date

**SEE PAGE 1**

Tolerances Unless otherwise specifically noted, the following are default tolerances:  
**2-places 3-places Angular**  
**+/- 0.02" +/- 0.005" +/- 1'**  
 Metric: Shown in [ ] refers to equivalent English Dim Tol  
 "REF." or an Asterisk (\*) = Non-Toleranced Reference Dimension, shown for clarification purposes only.  
 NOTE: All tolerances are Non-Cumulative.

**PROPRIETARY INFORMATION** This Engineering Drawing, and the information contained herein, is proprietary to Cole Hersee Company and may not be disclosed, re-produced, or in any other way transferred or communicated to any other party without the express written consent of an authorized representative of Cole Hersee Company.

**Special Characteristics:**  
 Critical Characteristic, relating to Safety and/or Regulatory Compliance  
 Significant Characteristic relating to Process Control  
 Control Dimension relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer

**Cole Hersee Co.**  
 20 Old Colony Ave., South Boston, MA, 02127  
 Phn: 617-268-2100 Web: www.colehersee.com

**Description:**  
**LVD,MINI,10A**

**Drawing / Part No.:** **48610** **Current Rev.:** **G**

FORM CHT-6 (2/07)

Used On or Ref.: **EX28439A**

Scale: 1:1

Drawn By: **CN**

Date Drawn: **03/18/09**

**Pg. 2 of 2**

4

3

2

1

↑