






- NOTES:
1. ALL DIMENSION ARE REFFRENCE ONLY UNLESS NOTED OTHERWISE
 2. SPRING FORCE 10 LBS [44.4 N] MIN AT FULL CUP TRAVEL
 3. ALL PLASTIC PARTS Black IN COLOR
 4. MATERIAL: PA66 GF30 A3EG6
 - 5.PARTS 98460 PLUNGER; 87174 BRACKET & 81474 HOUSING TO MATCH IN COLOR AND FINISH

Revision Control Record				Rev.	Description of Change	ECN No.	Date	Note: unless noted otherwise all dimension are AFTER plating Tolerances Unless otherwise specifically noted, the following are default tolerances; 2-places 3-places Angular +/- 0.02"[0.50] +/- 0.005"[0.13] +/- 1' Unless otherwise specified dimensions are in inches Dimensions in brackets [] are in millimeters "REF" = Non-Toleranced Reference Dimension, shown for clarification purposes only. NOTE: All tolerances are Non-Cumulative.			PROPRIETARY INFORMATION All information contained herein, is proprietary to the Cole Hersee Company. Unauthorized use or reproduction is prohibited.		Special Characteristics:  Critical Characteristic, relating to Safety and/or Regulatory Compliance  Significant Characteristic relating to Process Control  Control Dimension relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer		  Phn: 617-268-2100 Web: www.colehersee.com	
Rev.	Description of Change	ECO No.	Date											Description: STOR-A-WAY 7 POLE		
E	REVISED SPRING	09443	1/27/09													
F	BOM CHANGE	11033	3/01/11													
G	REDESIGN 11750-03	10093	02/13/14													
H	REVISED NOTES	11202	11/05/14													
								FORM CHT-6 (1/12)	Used On or Ref.:	ABUCPROTO29083		Scale: 1:1	Drawn By: CM	Date Drawn: 01/29/2014	Pg.1 of 1	Current Rev. H