




NOTES:

1. ALL DIMENSIONS ARE REFERENCE ONLY
2. SPECIFICATIONS:
 - OPERATING VOLTAGE: 9-32VDC
 - CURRENT RATING: LOAD+ 10A AT 85°C
 - QUIESCENT CURRENT 2 mA MAX
 - OPERATING TEMPERATURE: -40°C TO 85°C
 - OVERCURRENT THRESHOLD: 12 - 17A
3. CONNECTOR PINOUT:
 - PIN1: UNUSED
 - PIN2: GROUND (BATTERY-)
 - PIN3: LOAD+
 - PIN4: BATTERY+
 - PIN5: TRIGGER
 - PIN6: UNUSED
 - PIN7: REDUNDANT GROUND (BATTERY-)
 - PIN8: REDUNDANT GROUND (BATTERY-)
4. MATING CONNECTOR: DEUTSCH P/N DT06-08S
5. MATING PINS: DEUTSCH P/N 0462-201-16141
6. UNUSED PINS SHOULD BE SEALED WITH BLANKING PIN- DEUTSCH P/N: 114017
7. ONLY ONE GROUND (BATTERY -) CONNECTION IS REQUIRED FOR PROPER OPERATION. ALL OTHER GROUNDS ARE REDUNDANT
8. SEALED TO IP67 (PROVIDED BLANKING PINS USED)

48736-01	20 MIN	4 MIN	20 SEC	20 SEC	12805
48736	20 MIN	4 MIN	20 SEC	20 SEC	NONE
PART NUMBER	TIME DELAY 1	TIME DELAY 2	TIME DELAY 3	TIME DELAY 4	KIT

Revision Control Record				Rev.	Description of Change	ECN No.	Date	Tolerances Unless otherwise specifically noted, the following are default tolerances:			PROPRIETARY INFORMATION This Engineering Drawing, and the information contained herein, is proprietary to Cole Hersee Company and may not be disclosed, re-produced, or in any other way transferred or communicated to any other party without the express written consent of an authorized representative of Cole Hersee Company.			Special Characteristics:			Cole Hersee Co. 20 Old Colony Ave., South Boston, MA, 02127 Phn: 617-268-2100 Web: www.colehersee.com		
Rev.	Description of Change	ECN No.	Date					2-places +/- 0.02"	3-places +/- 0.005"	Angular +/- 1°				CC Critical Characteristic, relating to Safety and/or Regulatory Compliance	X Significant Characteristic relating to Process Control	KC Control Dimension relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer	Description: TRAILER LIGHT TIMER		
A	RELEASED DRAWING	10368	11/2/10														Drawing / Part No.: 48736		Current Rev. A
							</												