

24612-13	12	3.8	INTERMITTENT	14	8.5	COPPER	F	ASSEMBLED ©			IP6X	
©												
©												
©												
24612-10	12	18.6	CONTINUOUS	14	7.5	SILVER	F	ASSEMBLED ⑤			IP6X	
©												
©												
©												
©												
©												
©												
24612-03	12	3.8	INTERMITTENT	14	8.5	COPPER	L	ASSEMBLED ©			IP6X	
©												
©												
©												
©												
24612	12	18.6	CONTINUOUS	14	7.5	SILVER	L	ASSEMBLED ©			IP6X	
PART NO	V DC	OHMS	DUTY CYCLE	MAX VOLT.	PULL-IN VOLT.	CONTACT MATERIAL	BRACKET STYLE	HARDWARE NOTE 7			MOISTURE PROTECTION	ADDITIONAL NOTES
	COIL RATINGS											

Revision Control Record

Rev.	Description of Change	ECN No.	Date

Revision Control Record

Rev.	Description of Change	ECN No.	Date

Tolerances

Unless otherwise specifically noted, the following are default tolerances;
• 2-place Decimal Dimensions +/- .02"
• 3-place Decimal Dimensions +/- .005"
• Angular Dimensions +/- 1.0 Deg.
• Metric: Refer to equivalent English Dimension Tolerance
>>> NOTE: All tolerances are Non-Cumulative. <<<

Dimensional Units

All dimensions are expressed in inches except those shown in brackets (xxx) are expressed in millimeters

"REF." or an Asterisk (*)

= Non-Toleranced Reference Dimension, shown for clarification purposes only.

Used On or Ref.:

EX27922-B12

Scale:

1:1

PROPRIETARY INFORMATION

This Engineering Drawing, and the information contained herein, is proprietary to Cole Hersee Company and may not be disclosed, re-produced, or in any other way transferred or communicated to any other party without the express written consent of an authorized representative of Cole Hersee Company.

DESIGN CONTROL

It is the responsibility of the individual using / referencing this drawing to assure that the noted design revision level agrees with the revision level of the Controlled Document (Master Drawing). This is a NON-CONTROLLED DOCUMENT unless otherwise specifically noted.

DO NOT SCALE

- Dimensional variation may occur during printing / reproduction.

Drawn By:

GA

Date Drawn:

5/2/03

Special Characteristics:

CC

Critical Characteristic, relating to Safety and/or Regulatory Compliance

X

Significant Characteristic relating to Process Control (SPC)

KC

Key Characteristic relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer


(Note that the identification of any Characteristics as being "Special" does not alter the requirement that ALL specified dimensions & tolerances must be met.)

Responsible Engineer:

N/A

Pg.

2 OF 2



Cole Hersee Co.
20 Old Colony Ave., South Boston, MA, 02127
Phn: 617-268-2100 Web: www.colehersee.com

Description:

SOLENOID, 12V,SPST,N.O

Drawing / Part No.:

24612-CHART

Current Rev.

SEE PAGE 1