



PIN NUMBER	CIRCUIT	12VDC RESISTIVE LOAD
2	NOT USED	
3	ACCESSORY	10 AMPS
4 & 5	IGNITION	10 AMPS
1 & 6	BATTERY	
PINS 1 & 6 CONNECTED TOGETHER INTERNALLY		
PINS 4 & 5 CONNECTED TOGETHER INTERNALLY		

Revision Control Record				Rev.	Description of Change	ECN No.	Date	Note: unless noted otherwise all dimension are AFTER plating Tolerances Unless otherwise specifically noted, the following are default tolerances;			PROPRIETARY INFORMATION All information contained herein, is proprietary to the Cole Hersee Company. Unauthorized use or reproduction is prohibited.		Special Characteristics:		Littelfuse®	
Rev.	Description of Change	ECN No.	Date					2-places	3-places	Angular			CC	Critical Characteristic, relating to Safety and/or Regulatory Compliance	Description:	Phn: 617-268-2100 Web: www.colehersee.com
A	NEW RELEASE	15031	10/16/15					+/- 0.02"[0.50]	+/- 0.005"[0.13]	+/- .1°			X	Significant Characteristic relating to Process Control	SW,ROT,IGN,PLSTC	
B	CHANGE LEVER	16318	08/25/16					Unless otherwise specified dimensions are in inches Dimensions in brackets [] are in millimeters "REF" = Non-Toleranced Reference Dimension, shown for clarification purposes only. NOTE: All tolerances are Non-Cumulative.					CC	Control Dimension relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer		
								FORM CHT-6 (1/12) Used On or Ref.: EX29233A			Scale: 1:1	Drawn By: CM	Date Drawn: 07/29/15	Pg.1 of 1	Drawing / Part No.: 95060-98	Current Rev. B