














PIN NUMBER	CIRCUIT	12VDC RESISTIVE LOAD
2	START	5 AMPS
3	ACCESSORY	10 AMPS
4 & 5	IGNITION	10 AMPS
1 & 6	BATTERY	
PINS 1 & 6 CONNECTED TOGETHER INTERNALLY PINS 4 & 5 CONNECTED TOGETHER INTERNALLY		

NOTES:
1. TOLERANCES PLUS OR MINUS 0.015 [0.38]
2. ELECTRICAL CONTACT AREA SEALED TO IP67
3. BACK OF SWITCH IS SEALED WHEN MATING CONNECTOR IS INSTALLED.
4. FOR RESISTIVE LOAD RATING SEE CHART OR BACK OF SWITCH
5. PIN LOCATIONS SEE CHART.
6. SWITCH HOUSING: BLACK THERMOPLASTIC; STATIONARY CONTACTS: COPPER
   SHAFT: ZINC DIE CAST; KNOB: BLACK PLASTIC WITH WHITE INDICATOR
7. SWITCH TESTED TO SAE J259.
8. SW. MUST NOT BREAK CIRCUIT OR BE DAMAGED IF TORQUED TO 15 IN-LBS [1.69Nm]

Revision Control Record

Rev.	Description of Change	ECN No.	Date
A	RELEASED DRAWING	12352	01/22/13

Rev.	Description of Change	ECN No.	Date

Tolerances Unless otherwise specifically noted, the following are default tolerances;

2-places +/- 0.02" | 3-places +/- 0.005" | Angular +/- 1°

Metric: Shown in [ ] refers to equivalent English Dim Tol

"REF." or an Asterisk (*) = Non-Toleranced Reference Dimension, shown for clarification purposes only.

NOTE: *All tolerances are Non-Cumulative.*

PROPRIETARY INFORMATION
This Engineering Drawing, and the information contained herein, is proprietary to Cole Hersee Company and may not be disclosed, re-produced, or in any other way transferred or communicated to any other party without the express written consent of an authorized representative of Cole Hersee Company.

Special Characteristics:
- CC: Critical Characteristic, relating to Safety and/or Regulatory Compliance
- X: Significant Characteristic relating to Process Control
- KC: Control Dimension relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer

FORM CHT-6 (2/07) | Used On or Ref.: EX28803 | Scale: 1:1 | Drawn BY: A.VISCO | Date Drawn: 11/26/2012 | Pg. 1 of 1

Cole Hersee Co.
20 Old Colony Ave., South Boston, MA, 02127
Phn: 617-268-2100 Web: www.colehersee.com

Description: **SW, ROT, 3POS, KNOB**

Drawing / Part No.: **95062-25**

Current Rev.: **A**