

Application Note: Rice Cooker Lid Lock With Position-Sensing Reed Switches



#### Introduction

Electric rice cookers are popular appliances that are used for cooking rice. These are pressure cookers that rely on a properly sealed compartment which maintains a high pressure. The pressure built up within the rice cooker compartment can be high enough to blow open the cooker lid if the lid is not properly locked in place when closed.

The position sensing lid lock ensures that the lid is securely locked in place.

### Solution

A reed switch is used as a position sensor to detect when the lid is properly closed in place.

Table	1: 3	Suggested	l Prod	ucts

Suggested Products
FLEX-14 Reed Switch
MDCG-4 Reed Switch
MDSM-10 Reed Switch
59170 Overmolded Reed Switch
59135 Reed Sensor
59145 Reed Sensor

#### FEATURES AND BENEFITS:

- Switch activation does not require physical contact
- Switch contacts are within a hermetically sealed capsule
- Resistant to moisture, dust, and other foreign objects
- High operating temperature
- Reliable switching
- Long lifetime

### **How It Works**

A reed switch is a magnetically operated switch that is normally open when there is no magnetic field present within its defined sensing or "activation" range. When a magnetic field is present in proper alignment and of sufficient strength, the contacts of the reed switch will close and complete the circuit. If the magnetic field is removed, out of proper alignment, or weakened in strength, the contacts of the reed switch will open again, disconnecting the circuit.



Figure 1: Block Diagram of Application

A permanent magnet is embedded within the handle of the rice cooker lid and is used to provide the magnetic field to operate a reed switch located within the electronic assembly in the rice cooker lid. When the lid is not in the "locked" position, the magnet in the handle is not properly aligned to the reed switch, thus keeping the reed switch contacts open. The electronic control unit is signaled that the lid is not properly closed and will notify the user of this. Only when the handle is in the "locked" position, the reed switch contacts close and signals the control unit that the lid is properly closed.



# Application Note: Rice Cooker Lid Lock With Position-Sensing Reed Switches



Figure 2. Mechanical Structure- Position Sensing in Rice Cooker Lid Lock

## **Beyond Sensing, Littelfuse® Offers Circuit Protection Solutions**

In addition to sensor products, Littelfuse offers the world's broadest and deepest portfolio of circuit protection and power control solutions.

Littelfuse recommends the following products for use in this application:

Application Example	Product Series				
Power Control					
Heater AC Power Control	Q60xxxH6 Thyristors				
Circuit Protection					
	TMOV, LA, UltraMOV Varistors				
AC Mains	3AG, 5x20mm Fuses				
	Holders, Blocks, Clips				
Touch Screen/Display	SP1001, SP1003 Diode Arrays				
Panel	Multilayer Varistors				

**Table 2: Circuit Protection and Power Control Solutions** 



Littelfuse, Inc. 8755 West Higgins Road, Suite 500 Chicago, IL 60631 USA Phone: (773) 628-1000 www.littelfuse.com