


IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)
CB SCHEME

CB TEST CERTIFICATE

Product	Voltage Maintained Thermal cut-out
Name and address of the applicant	LITTELFUSE INC SUITE 500 8755 W HIGGINS RD CHICAGO, IL 60631 USA
Name and address of the manufacturer	LITTELFUSE INC SUITE 500 8755 W HIGGINS RD CHICAGO, IL 60631 USA
Name and address of the factory	LITTELFUSE ELECTRONICS (KUNSHAN) CO., LTD NO.389 CENTRAL AVE, ZONE B, EPZ, KUNSHAN JIANGSU 215312 CHINA
<i>Note: When more than one factory, please report on page 2</i>	<input type="checkbox"/> Additional Information on page 2
Ratings and principal characteristics	A, B, D, E, F or TAC15-, ww/o, 12-, f/b 72, 77, 82, 85 or 90 Contact: 12 Vdc, 25 A Load Type: Resistive Cycles: 6,000 Opening Temperature: 72, 77, 82, 85 or 90 °C See Page 2
Trademark (if any)	
Type of Customer's Testing Facility (CTF) Stage used	
Model / Type Ref.	A, B, D, E, F, TAC15, a, b, d, e, TAC6 See Page 2
Additional information (if necessary may also be reported on page 2)	Additionally evaluated to EN 60730-2-9:2010, EN 60730-1:2011; National Differences specified in the CB Test Report. <input type="checkbox"/> Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 60730-1:2010, IEC 60730-2-9:2008/AMD1:2011, IEC 60730-2-9:2008
As shown in the Test Report Ref. No. which forms part of this Certificate	4788061316-20180822 issued on 2018-08-22

This CB Test Certificate is issued by the National Certification Body



- UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL (Denko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2018-08-23

Signature:

Jan-Erik Storgaard



Ref. Certif. No.

DK-75944-UL

Model Details:

TAC15-, ww/o, 12-, f/b 72, 77, 82, 85 or 90

TAC6-, ww/o, 12-, f/b 72, 77, 82 or 85

All models in TAC6 and TAC15 Series may have prefix MHP- and one or more suffixes may be added. One or more suffixes may be added to the model number to denote different properties such as lead configuration, different lead length, and/or different shipping packaging method. Halogen-free models may be indicated by the letter "H".

ww/o: with or without

f/b: followed by

Model Nomenclature:

MHP-TAC	15	-	12	-	xx
I	II		III		IV

- I - Basic type designation
TAC
May have prefix MHP-
- II - Manufacture Specified Holding Current Rating, (A)
15 or 6
- III - Voltage Rating in DC, (V)
12
- IV - Depends on space, it is optional
Set point temperature rating, (°C)
72, 77, 82, 85 or 90
90 is only for TAC15

Ratings:

a, b, d, e or TAC6-, ww/o, 12-, f/b 72, 77, 82 or 85

Contact: 12 Vdc, 12 A

Load Type: Resistive

Cycles: 6,000

Opening Temperature: 72, 77, 82 or 85 °C

Additional information (if necessary)



- UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2018-08-23

Signature:

Jan-Erik Storgaard