



JDYX8.E10480 Fuses, Supplemental Certified for Canada - Component

[Page Bottom](#)

Fuses, Supplemental Certified for Canada - Component

[See General Information for Fuses, Supplemental Certified for Canada - Component](#)

LITTELFUSE INC

E10480

SUITE 500
8755 W HIGGINS RD
CHICAGO, IL 60631 USA

Supplemental fuses

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
208*	4.5 x 15 (0.18 x 0.59)	1.5 - 10	350Vac	100
208*+	4.5 x 15 (0.18 x 0.59)	0.1 - 1	350Vac	100
208003	4.5 x 15 (0.18 x 0.59)	3	140Vdc	150
209xxx*	-	0.25 - 7	350Vac	100
210*	5 x 20 (0.20 x 0.79)	0.2 - 0.4	250Vac	1500
215*	5 x 20 (0.20 x 0.79)	0.2 - 0.4	250Vac	1500
215-SR	5 x 20 (0.20 x 0.79)	0.2 - 0.4	250Vac	1500
217*+, 617*	5 x 20 (0.20 x 0.79)	0.05 - 0.1	250Vac	35
		0.4 - 1.6	250Vac	35
		6.3	250Vac	50
		8 - 10	250Vac	100
		6.3	60Vdc	70
		2.0 - 3.15	75Vdc	70
		0.032 - 0.04	250Vac	35
		0.125 - 0.315	250Vac	35
		2.0 - 5.0	250Vac	50
		2.0 - 5.0	60Vdc	70
219xxxA*+	5 x 20 (0.20 x 0.79)	4 - 6.3	250Vac	150
		4 - 6.3	350Vac	100
		0.04 - 0.1	250Vac	150
		0.125 - 0.63	250Vac	150
		0.8 - 3.15	250Vac	150

221*	5 x 20 (0.20 x 0.79)	0.2 - 0.4	250Vac	1500
314010MX280	6.35 x 31.75 (0.25 x 1.25)	10	125Vac	10000
		10	125Vdc	10000
		10	250Vac	750
		10	280Vac	350
449*	-	0.375 - 5	125Vac	50
		0.375 - 5	125Vdc	50
		7	72Vac	50
		7	60Vdc	50
458*	-	7	63Vdc	50
		8 - 10	63Vdc	50
		1 - 6.3	75Vdc	50
		1 - 3.5	48Vac	50
		4 - 7	32Vac	50
		8 - 10	32Vac	50
458xxxW*	-	1 - 7	63Vdc	50
A210*+	5 x 20 (0.20 x 0.79)	0.2 - 0.4	250Vac	1500
FK1	16.3 x 11.8 x 3.8 (0.64 x 0.46 x 0.15)	1 - 15	32Vdc	450
FKS32	20.0 x 19.1 x 5.0 (0.79 x 0.75 x 0.20)	1 - 40	32Vdc	1000
FP1	12.8 x 11.8 x 3.8 (0.50 x 0.46 x 0.15)	1 - 15	32Vdc	450
TAC	20.0 x 19.1 x 5.0 (0.79 x 0.75 x 0.20)	1 - 10	58Vdc	1000
		40	58Vdc	1000
		15 - 30	58Vdc	1000

Supplemental fuses: pigtail leads

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
208E*+	4.5 x 15 (0.18 x 0.59)	0.1 - 1	350Vac	100
210xxxE*, 210xxxSP*	5 x 20 (0.20 x 0.79)	0.2 - 0.4	250Vac	1500
215xxxE*, 215xxxSP*	5 x 20 (0.20 x 0.79)	0.2 - 0.4	250Vac	1500
217xxxE*, 217xxxSP, 617xxxE, 617xxxSP				
	5 x 20 (0.20 x 0.79)	0.4 - 1.6	250Vac	35
		6.3	250Vac	50
		8 - 10	250Vac	100
		6.3	60Vdc	70
		2.0 - 3.15	75Vdc	70
		0.05 - 0.1	250Vac	35

		0.032 - 0.04	250Vac	35
		0.125 - 0.315	250Vac	35
		2.0 - 5.0	250Vac	50
		2.0 - 5.0	60Vdc	70
220007*+	4.5 x 15 (0.18 x 0.59)	3	350Vac	100
		3	140Vdc	160
		3	530Vac	60
220019*+	4.5 x 15 (0.18 x 0.59)	3	350Vac	100
		3	125Vdc	100
2205*	4.5 x 15 (0.18 x 0.59)	0.25 - 2.5	125Vac	10000
		0.25 - 2.5	250Vac	35
		0.25 - 2.5	600Vac	60
		0.25 - 1	600Vac	40
221xxxE*, 221xxxSP*	5 x 20 (0.20 x 0.79)	0.2 - 0.4	250Vac	1500
312	6.35 x 31.75 (0.25 x 1.25)	30	32Vdc	300
		30	32Vac	300
318	6.35 x 31.75 (0.25 x 1.25)	12	32Vdc	300
		15 - 30	32Vdc	300
		12	32Vac	300
		15 - 30	32Vac	300
324010MX280	6.35 x 31.75 (0.25 x 1.25)	10	125Vac	10000
		10	125Vdc	10000
		10	250Vac	750
		10	280Vac	350
A210xxxE*+, A210xxxSP				
	5 x 20 (0.20 x 0.79)	0.2 - 0.4	250Vac	1500

Supplemental fuses: pigtail leads, cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
478E, 479E	4.5 x 15.0 (0.18 x 0.59)	0.5 - 1.0	600Vac	32
		1.1 - 3.5	600Vac	32
		4 - 10	600Vac	32

Supplemental fuses: pigtail leads, filled-tube

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
210xxxE*, 210xxxSP*	5 x 20 (0.20 x 0.79)	4.0 - 12	250Vac	1500

		0.125 - 0.16	250Vac	50000
		4.0 - 12	250Vac	50000
		15 - 16	250Vac	500
		20	250Vac	400
		25	250Vac	300
		1 - 2	500Vac	100
		4 - 6.3	305Vac	100
		0.125 - 0.16	250Vac	1500
		0.5 - 0.8	250Vac	1500
		0.5 - 0.8	250Vac	50000
		0.125 - 0.8	250Vac	210%
		1.0 - 3.15	250Vac	1500
		1.0 - 3.15	250Vac	50000
		1.0 - 3.15	250Vac	210%
		1 - 2	500Vac	210%
		4 - 6.3	305Vac	210%
		4.0 - 12	250Vac	210%
		15 - 16	250Vac	275%
		20	250Vac	275%
		25	250Vac	210%
215xxxE*, 215xxxSP*	5 x 20 (0.20 x 0.79)	4.0 - 12	250Vac	1500
		0.125 - 0.16	250Vac	50000
		4.0 - 12	250Vac	50000
		15 - 16	250Vac	500
		20	250Vac	400
		25	250Vac	300
		1 - 2	500Vac	100
		4 - 6.3	305Vac	100
		0.125 - 0.16	250Vac	1500
		0.5 - 0.8	250Vac	1500
		0.5 - 0.8	250Vac	50000
		0.125 - 0.8	250Vac	210%
		1.0 - 3.15	250Vac	1500
		1.0 - 3.15	250Vac	50000
		1.0 - 3.15	250Vac	210%
		1 - 2	500Vac	210%
		4 - 6.3	305Vac	210%
		4.0 - 12	250Vac	210%
		15 - 16	250Vac	275%
		20	250Vac	275%
		25	250Vac	210%

216xxxE*, 216xxxSP*, 616xxxE*, 616XXXSP*				
	5 x 20 (0.20 x 0.79)	1 - 1.25	300Vac	150
		12.5 - 16.0	250Vac	750
		12.5 - 16.0	125Vac	1000
		12.5 - 16.0	350Vac	100
		0.05 - 0.125	250Vac	35
		0.16 - 0.315	250Vac	35
		0.4 - 0.8	250Vac	35
		1.0 - 3.15	250Vac	1500
		4 - 10	250Vac	1500
		1.25 - 3.15	60Vdc	500
		4 - 6.3	60Vdc	500
221xxxE*, 221xxxSP*				
	5 x 20 (0.20 x 0.79)	4.0 - 12	250Vac	1500
		0.125 - 0.16	250Vac	50000
		4.0 - 12	250Vac	50000
		15 - 16	250Vac	500
		20	250Vac	400
		25	250Vac	300
		1 - 2	500Vac	100
		4 - 6.3	305Vac	100
		0.125 - 0.16	250Vac	1500
		0.5 - 0.8	250Vac	1500
		0.5 - 0.8	250Vac	50000
		0.125 - 0.8	250Vac	210%
		1.0 - 3.15	250Vac	1500
		1.0 - 3.15	250Vac	50000
		1.0 - 3.15	250Vac	210%
		1 - 2	500Vac	210%
		4 - 6.3	305Vac	210%
		4.0 - 12	250Vac	210%
		15 - 16	250Vac	275%
		20	250Vac	275%
		25	250Vac	210%
324*, WP91768-17, WP91768-18, WP91768-19, 324xxxSP				
	6.35 x 31.75 (0.25 x 1.25)	20	125Vac	10000
		20	125Vdc	10000
		20	250Vac	1000
		20	300Vac	200
		25 - 30	125Vac	400
		25 - 30	125Vdc	400

		25 - 30	250Vac	100
		25 - 30	75Vdc	1000
		40	250Vac	1000
		40	150Vdc	400
324015MX280	6.35 x 31.75 (0.25 x 1.25)	15	125Vac	10000
		15	125Vdc	10000
		15	250Vac	750
		15	280Vac	350
324020MX280	6.35 x 31.75 (0.25 x 1.25)	20	125Vac	10000
		20	125Vdc	10000
		20	250Vac	1000
		20	280Vac	350
		20	300Vac	200
324025MX280	6.35 x 31.75 (0.25 x 1.25)	25	125Vac	400
		25	125Vdc	400
		25	250Vac	100
		25	75Vdc	1000
		25	280Vac	50
332*	6.35 x 31.75 (0.25 x 1.25)	1 - 10	250Vac	100
		1 - 10	125Vdc	100
		1 - 10	72Vdc	200
		1 - 10	250Vac	250%
		1 - 10	125Vdc	250%
377	5 x 20 (0.20 x 0.79)	1 - 3.15	400Vac	500
		1 - 3.15	600Vac	100
		1 - 3.15	400Vdc	1500
		4 - 5	600Vac	100
		4 - 5	400Vdc	500
		6.3 - 12	500Vac	100
		10 - 12	400Vdc	500
		16	500Vac	100
		16	400Vdc	400
		0.5 - 0.8	600Vac	100
		0.5 - 0.8	400Vac	500
		0.5 - 0.8	400Vdc	1500
		6.3 - 8	400Vdc	500
477	5 x 20 (0.20 x 0.79)	1 - 3.15	400Vac	500
		1 - 3.15	600Vac	100

		1 - 3.15	400Vdc	1500
		4 - 5	600Vac	100
		4 - 5	400Vdc	500
		6.3 - 12	500Vac	100
		10 - 12	400Vdc	500
		16	500Vac	100
		16	400Vdc	400
		0.5 - 0.8	600Vac	100
		0.5 - 0.8	400Vac	500
		0.5 - 0.8	400Vdc	1500
		6.3 - 8	400Vdc	500
506	6.35 x 31.75 (0.25 x 1.25)	15 - 20	600Vdc	10000
508	6.35 x 31.75 (0.25 x 1.25)	0.315 - 1	1000Vac	10000
		0.315 - 1	1000Vdc	10000
508xxxMX6	6.35 x 31.75 (0.25 x 1.25)	0.315 - 0.5	600Vac	10000
		0.315 - 0.5	600Vdc	10000
		1.0	600Vac	10000
		1.0	600Vdc	10000
747	4.4 x 11 (0.17 x 0.43)	1.25	250Vac	50
A210xxxE*+, A210xxxSP				
	5 x 20 (0.20 x 0.79)	4.0 - 12	250Vac	1500
		0.125 - 0.16	250Vac	50000
		4.0 - 12	250Vac	50000
		15 - 16	250Vac	500
		20	250Vac	400
		25	250Vac	300
		1 - 2	500Vac	100
		4 - 6.3	305Vac	100
		0.125 - 0.16	250Vac	1500
		0.5 - 0.8	250Vac	1500
		0.5 - 0.8	250Vac	50000
		0.125 - 0.8	250Vac	210%
		1.0 - 3.15	250Vac	1500
		1.0 - 3.15	250Vac	50000
		1.0 - 3.15	250Vac	210%
		1 - 2	500Vac	210%
		4 - 6.3	305Vac	210%
		4.0 - 12	250Vac	210%

		15 - 16	250Vac	275%
		20	250Vac	275%
		25	250Vac	210%

Supplemental fuses: pigtail leads, filled-tube, cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
328xxxE	6.35 x 31.75 (0.25 x 1.25)	21	300Vac	200
		21	100Vdc	200
487E*+	5 x 20 (0.20 x 0.79)	8 - 16	420Vac	200
		8 - 16	420Vdc	300
487SP*+	5 x 20 (0.20 x 0.79)	8 - 16	420Vac	200
		8 - 16	420Vdc	300
688 may be followed by P, may be followed by E				
	6.3 x 25.2 (0.25 x 0.99)	15 - 30	70Vdc	2500
		5 - 10	70Vdc	2500
777	4.4 x 11 (0.17 x 0.43)	1.25	250Vac	50
835 E %	5 x 20 (0.20 x 0.79)	5 - 8	250Vac	1500
835 SP %	5 x 20 (0.20 x 0.79)	5 - 8	250Vac	1500

Supplemental fuses: filled-tube

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
210*	5 x 20 (0.20 x 0.79)	0.125 - 0.16	250Vac	50000
		4.0 - 12	250Vac	50000
		15 - 16	250Vac	500
		20	250Vac	400
		25	250Vac	300
		1 - 2	500Vac	100
		4 - 6.3	305Vac	100
		0.125 - 0.16	250Vac	1500
		0.5 - 0.8	250Vac	1500
		0.5 - 0.8	250Vac	50000
		0.125 - 0.8	250Vac	210%
		1.0 - 3.15	250Vac	1500
		1.0 - 3.15	250Vac	50000
		1.0 - 3.15	250Vac	210%
		1 - 2	500Vac	210%
		4 - 6.3	305Vac	210%

		4.0 - 12	250Vac	1500
		4.0 - 12	250Vac	210%
		15 - 16	250Vac	275%
		20	250Vac	275%
		25	250Vac	210%
215*	5 x 20 (0.20 x 0.79)	0.125 - 0.16	250Vac	50000
		4.0 - 12	250Vac	50000
		15 - 16	250Vac	500
		20	250Vac	400
		25	250Vac	300
		1 - 2	500Vac	100
		4 - 6.3	305Vac	100
		0.125 - 0.16	250Vac	1500
		0.5 - 0.8	250Vac	1500
		0.5 - 0.8	250Vac	50000
		0.125 - 0.8	250Vac	210%
		1.0 - 3.15	250Vac	1500
		1.0 - 3.15	250Vac	50000
		1.0 - 3.15	250Vac	210%
		1 - 2	500Vac	210%
		4 - 6.3	305Vac	210%
		4.0 - 12	250Vac	1500
		4.0 - 12	250Vac	210%
		15 - 16	250Vac	275%
		20	250Vac	275%
		25	250Vac	210%
215-SR	5 x 20 (0.20 x 0.79)	2.5 - 5.0	250Vac	50000
		2.5 - 5.0	250Vac	1500
		0.125 - 0.16	250Vac	50000
		0.125 - 0.16	250Vac	1500
		0.5 - 0.8	250Vac	1500
		0.5 - 0.8	250Vac	50000
		0.125 - 0.8	250Vac	210%
		1.0 - 3.15	250Vac	1500
		1.0 - 3.15	250Vac	50000
		1.0 - 3.15	250Vac	210%
		1.0 - 2.0	500Vac	100
		1.0 - 2.0	500Vac	210%
216*+, 616*	5 x 20 (0.20 x 0.79)	1 - 1.25	300Vac	150
		12.5 - 16.0	250Vac	750

		12.5 - 16.0	125Vac	1000
		12.5 - 16.0	350Vac	100
		0.05 - 0.125	250Vac	35
		0.16 - 0.315	250Vac	35
		0.4 - 0.8	250Vac	35
		1.0 - 3.15	250Vac	1500
		4 - 10	250Vac	1500
		1.25 - 3.15	60Vdc	500
		4 - 6.3	60Vdc	500
221*	5 x 20 (0.20 x 0.79)	0.125 - 0.16	250Vac	50000
		4.0 - 12	250Vac	50000
		15 - 16	250Vac	500
		20	250Vac	400
		25	250Vac	300
		1 - 2	500Vac	100
		4 - 6.3	305Vac	100
		0.125 - 0.16	250Vac	1500
		0.5 - 0.8	250Vac	1500
		0.5 - 0.8	250Vac	50000
		0.125 - 0.8	250Vac	210%
		1.0 - 3.15	250Vac	1500
		1.0 - 3.15	250Vac	50000
		1.0 - 3.15	250Vac	210%
		1 - 2	500Vac	210%
		4 - 6.3	305Vac	210%
		4.0 - 12	250Vac	1500
		4.0 - 12	250Vac	210%
		15 - 16	250Vac	275%
		20	250Vac	275%
		25	250Vac	210%
314*, WP91768-117, WP91768-118, WP91768-119,314xxxSP				
	6.35 x 31.75 (0.25 x 1.25)	20	125Vac	10000
		20	125Vdc	10000
		20	250Vac	1000
		20	300Vac	200
		25 - 30	125Vac	400
		25 - 30	125Vdc	400
		25 - 30	75Vdc	1000
		25 - 30	250Vac	100
		40	250Vac	1000

		40	150Vdc	400
314015MX280	6.35 x 31.75 (0.25 x 1.25)	15	125Vac	10000
		15	125Vdc	10000
		15	250Vac	750
		15	280Vac	350
314020MX280	6.35 x 31.75 (0.25 x 1.25)	20	125Vac	10000
		20	125Vdc	10000
		20	250Vac	1000
		20	280Vac	350
		20	300Vac	200
314025MX280	6.35 x 31.75 (0.25 x 1.25)	25	125Vac	400
		25	125Vdc	400
		25	250Vac	100
		25	75Vdc	1000
		25	280Vac	50
505, 605	6.35 x 31.75 (0.25 x 1.25)	10 - 12	450Vac	20000
		10 - 12	250Vdc	1000
		15 - 16	500Vac	50000
		15 - 16	500Vdc	20000
		20 - 30	500Vdc	20000
		20 - 30	500Vac	30000
A210*+	5 x 20 (0.20 x 0.79)	0.125 - 0.16	250Vac	50000
		4.0 - 12	250Vac	50000
		15 - 16	250Vac	500
		20	250Vac	400
		25	250Vac	300
		1 - 2	500Vac	100
		4 - 6.3	305Vac	100
		0.125 - 0.16	250Vac	1500
		0.5 - 0.8	250Vac	1500
		0.5 - 0.8	250Vac	50000
		0.125 - 0.8	250Vac	210%
		1.0 - 3.15	250Vac	1500
		1.0 - 3.15	250Vac	50000
		1.0 - 3.15	250Vac	210%
		1 - 2	500Vac	210%
		4 - 6.3	305Vac	210%
		4.0 - 12	250Vac	1500
		4.0 - 12	250Vac	210%

		15 - 16	250Vac	275%
		20	250Vac	275%
		25	250Vac	210%
FK3	33.9 x 29.8 x 9.1 (1.33 x 1.17 x 0.36)	20 - 50	80Vdc	1000
FKS	19.9 x 19.0 x 5.0 (0.78 x 0.75 x 0.20)	3 - 20	80Vdc	1000
		25 - 30	80Vdc	750

Supplemental fuses: filled-tube, cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
328	6.35 x 31.75 (0.25 x 1.25)	21	300Vac	200
		21	100Vdc	200
487*+	5 x 20 (0.20 x 0.79)	8 - 16	420Vac	200
		8 - 16	420Vdc	300
688	6.3 x 25.2 (0.25 x 0.99)	15 - 30	70Vdc	2500
		5 - 10	70Vdc	2500
835 %	5 x 20 (0.20 x 0.79)	5 - 8	250Vac	1500

Supplemental fuses: filled-tube, surface mount

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
476	2.69 x 2.69 x 6.1 (0.11 x 0.11 x 0.24)	1 - 5	250Vac	100
		1 - 15	125Vdc	300
		6.3 - 15	125Vac	100
		6.3 - 15	125Vdc	300
		1 - 1.6	86Vdc	10000
		2 - 12	86Vdc	10000

Supplemental micro fuses

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
0400022*	3.118 x 1.670 x 0.835 (0.12 x 0.07 x 0.03)	12	24Vdc	100
251*	-	12 - 15	32Vac	50
		12 - 15	32Vdc	300
		0.062	250Vac	35
		2	150Vac	50
		2	150Vdc	100
		0.125 - 0.4	125Vac	50
		0.125 - 0.4	125Vdc	300
		0.5 - 1.6	125Vac	50

		0.5 - 1.6	125Vdc	300
		2.0 - 10	125Vac	50
		2.0 - 10	125Vdc	300
		0.062	125Vdc	300
		0.062	125Vac	50
252*	-	2.0 - 10	125Vac	50
		2.0 - 10	125Vdc	300
		12 - 15	32Vac	50
		12 - 15	32Vdc	300
		0.062	125Vac	50
		0.062	125Vdc	300
		0.5 - 1.6	125Vac	50
		0.125 - 0.4	125Vdc	300
		0.125 - 0.4	125Vac	50
		0.5 - 1.6	125Vdc	300
429*	3.18 x 1.5 (0.13 x 0.06)	4 - 7	24Vac	35
		4 - 7	24Vdc	35
437*	1.67 x 3.118 (0.07 x 0.12)	0.25 - 0.375	125Vac	50
		0.25 - 0.375	125Vdc	50
		1.75 - 2	63Vac	50
		1.75 - 2	63Vdc	50
		2.5 - 8	32Vac	50
		2.5 - 8	35Vdc	50
		0.5 - 1.5	63Vac	50
		0.5 - 1.5	63Vdc	50
438*	1.541 x 0.85 x 0.502 (0.06 x 0.03 x 0.02)	0.25 - 1.75	63Vdc	50
		0.25 - 1.75	32Vac	50
		2 - 5	32Vdc	50
		6	24Vdc	50
		2 - 6	12Vac	50
440*	3.2 x 1.62 x 0.818 (0.13 x 0.06 x 0.03)	0.25 - 0.375	125Vac	50
		0.25 - 0.375	125Vdc	50
		0.5	63Vac	50
		0.5	63Vdc	50
		1.0 - 1.5	50Vac	50
		1.0 - 1.5	50Vdc	50
		1.75 - 8.0	32Vac	50
		1.75 - 8.0	32Vdc	50
		0.75	63Vac	50

		0.75	63Vdc	50
441*	1.58 x 0.828 x 0.516 (0.06 x 0.03 x 0.02)	0.25 - 1.0	32Vdc	50
		1.25 - 6.0	32Vdc	50
445070	3.02 x 8.40 (0.12 x 0.33)	2	250Vac	100
469	3.12 x 1.62 x 0.90 (0.12 x 0.06 x 0.04)	1.0 - 2.0	63Vdc	60
		4.0 - 5.0	32Vdc	60
		6.0 - 8.0	24Vdc	60
		2.5 - 3.5	32Vdc	60
484*+	3.12 x 10.08 (0.12 x 0.40)	0.5 - 1.25	277Vac	100
		2.0 - 3.15	277Vac	100
		0.5 - 1.25	250Vdc	100
		2.0 - 3.15	250Vdc	100
		0.5 - 1.25	250Vac	100
		2.0 - 3.15	250Vac	100
491*	-	12 - 15	32Vac	50
		12 - 15	32Vdc	300
		0.062	250Vac	35
		0.125 - 0.4	125Vac	50
		0.125 - 0.4	125Vdc	300
		0.5 - 1.6	125Vac	50
		0.5 - 1.6	125Vdc	300
		2.0 - 10	125Vac	50
		2.0 - 10	125Vdc	300
		0.062	125Vac	50
		0.062	125Vdc	300
501*	3.118 x 1.670 x 0.835 (0.12 x 0.07 x 0.03)	10 - 20	32Vdc	150
501S*	3.118 x 1.670 x 0.502 (0.12 x 0.07 x 0.02)	10 - 20	32Vdc	150
ITV0412	5.4 x 3.2 (0.21 x 0.13)	12	36Vdc	50
ITV1212	5.4 x 3.2 (0.21 x 0.13)	12	36Vdc	50

Supplemental micro fuses: pigtail leads

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
263*	-	0.75 - 5	250Vac	50
		0.062	250Vac	50
		0.125 - 0.5	250Vac	50
275*, 276* (12A - 30A)				
	-	12 - 15	32Vac	50

		12 - 15	32Vdc	300
		20 - 30	32Vdc	300
		20 - 30	32Vac	100
875001C*	3.6 x 10 (0.14 x 0.39)	1	250Vac	50
876+	3.6 x 10 (0.14 x 0.39)	0.63 - 3.15	250Vac	35
		4	250Vac	40
		5	250Vac	50
		6.3	250Vac	63
		0.05 - 0.1	250Vac	35
		0.125 - 0.25	250Vac	35
		0.315 - 0.5	250Vac	35
876002SZ+	3.6 x 10 (0.14 x 0.39)	2	250Vac	35
876EC+	3.6 x 10 (0.14 x 0.39)	0.05 - 3.15	250Vac	35
		4	250Vac	40
		5	250Vac	50
877+, may be followed by SS, may be followed by EC.				
	3.6 x 10 (0.14 x 0.39)	0.25 - 3.15	250Vac	35
		4	250Vac	40
		5	250Vac	50
		6.3	250Vac	63

Supplemental micro fuses: pigtail leads, filled-tube

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
242xxxA	3.02 x 8.40 (0.12 x 0.33)	0.05 - 0.25	250Vac	4000
		0.05 - 0.25	250Vdc	4000
776	3.6 x 10 (0.14 x 0.39)	2.12	250Vac	100

Supplemental micro fuses: filled-tube

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
242	3.02 x 8.40 (0.12 x 0.33)	0.05 - 0.25	250Vac	4000
		0.05 - 0.25	250Vdc	4000

Supplemental micro fuses: filled-tube, surface mount

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
451xxxC \$	-	3 - 5	125Vac	50
		3 - 5	125Vdc	50
		3 - 5	32Vdc	300

Supplemental micro fuses: surface mount

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
0486.500NR, 0486.800NR, 0486001.NR, 04861.25NR, 048601.5NR, 0486002.NR, 048602.5NR, 0486003.NR, 0486004.NR, 0486005.NR, 0486007.NR				
	3.0 x 1.5 x 0.5 (0.12 x 0.06 x 0.02)	0.5 - 2.0	63Vdc	50
		2.5 - 3.0	32Vdc	50
		4.0 - 7.0	24Vdc	50
		4.0 - 7.0	32Vdc	50
443*	-	0.5 - 5	250Vac	50
450002*	-	0.5	125Vac	50
		0.5	125Vdc	50
450005*	-	3	125Vac	50
		3	125Vdc	50
		3	32Vdc	300
450007*	-	2	125Vac	50
		2	125Vdc	50
451*, \$	-	6.3 - 8	125Vac	50
		10	125Vac	35
		6.3 - 10	125Vdc	50
		6.3 - 10	32Vdc	300
		12 - 15	65Vac	50
		12 - 15	65Vdc	50
		12 - 15	24Vdc	300
		12 - 15	75Vdc	50
452*\$, 454*	-	0.375 - 5	125Vac	50
		0.375 - 5	125Vdc	50
		0.375 - 5	32Vdc	300
		6 - 12	72Vac	50
		6 - 12	60Vdc	50
		6 - 12	75Vdc	100
452xxx C \$	-	0.375 - 5	125Vac	50
		0.375 - 5	125Vdc	50
		2 - 3.5	32Vdc	300
453*, 490, 450011MR	-	6.3 - 8	125Vac	50
		10	125Vac	35
		6.3 - 10	125Vdc	50
		6.3 - 10	32Vdc	300
		12 - 15	65Vac	50
		12 - 15	65Vdc	50
		12 - 15	24Vdc	300
456*	-	20 - 30	125Vac	100

		20 - 30	65Vac	300
		20	100Vdc	300
		20 - 30	32Vdc	1000
		40	60Vdc	600
		20 - 30	72Vdc	500
		40	72Vdc	180
463	9.6 x 2.6 x 2.6 (0.38 x 0.10 x 0.10)	25 - 30	65Vac	300
		25 - 30	250Vac	100
		15 - 20	100Vdc	50
		25 - 30	72Vdc	500
		25 - 30	57Vdc	800
		25 - 30	48Vdc	1400
		25 - 30	32Vdc	1000
		25 - 30	12Vdc	2500
		15 - 20	65Vac	300
		15 - 20	250Vac	100
		15 - 20	32Vdc	1000
		15 - 20	72Vdc	500
		15 - 20	57Vdc	800
		15 - 20	48Vdc	1400
		15 - 20	12Vdc	2500
		25 - 30	100Vdc	50

\$ - May be followed by -L or -SN

% - With or without 1 to 2 prefix and with or without additional suffixes, may be followed by P may be followed by SP or E.

(a) - Followed by .500, 001, 01.5, 002, 02.5 or 3.15, with or without one prefix and with and without up to three additional suffix letters. The prefix or suffix serve as options such as apckaging , etc. and do not affect the electrical characteristics.

* - With or without one prefix character and with or without additional suffix characters that signify options that do not affect the electrical characteristics.

+ - May be followed by P which indicates the utilization of lead-free solder.

- - ** - Maybe followed by additional suffixes.

EC - Where suffix EC denotes epoxy coating over the body

SS - Where suffix SS denotes heat shrink tubing over the body.

Marking: Company name or tradename "LF" , model designation and the Recognized Component Mark for Canada, .
Last Updated on 2014-10-30

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide

Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".