

## Automotive Sensor Products

### Rotary Position Sensor – Hall



#### General Description

The sensor detects the shaft rotation and outputs the signal proportional to the shaft angle position.

#### Operation

##### Basic Principle

The sensor is assembled to a shaft with a defined angle position. When the driving shaft rotates, the magnet in the sensor rotates simultaneously interacting with the Hall Effect sensor which outputs a voltage proportional to the angle of rotation.

##### Packaging Options

Custom packaging can be provided to meet any need, please contact Littelfuse Engineering for details.

#### Features

- ◆ Magnetically operated position sensor
- ◆ Choice of angular sensing ranges available
- ◆ Analog and PWM outputs available
- ◆ Non-contact measuring
- ◆ Choice of clockwise or counterclockwise versions available
- ◆ Choice of connectors and terminals

#### Benefits

- ◆ High speed
- ◆ High immunity to outside magnetic interference
- ◆ Robust construction makes this sensor well suited to harsh environments

#### Applications

- ◆ Pedal position
- ◆ Absolute rotary encoder
- ◆ Throttle position
- ◆ EGR
- ◆ Flap valves
- ◆ Shaft position

## Automotive Sensor Products

## Functional Characteristics

Parameter			
Type			
Hall Effect Sensor	2D or 3D Hall		
Output	Analog		
Electrical			
Supply Voltage	5V ± 0.2 Vdc		
Output Voltage	0.5 to 4.5 Vdc		
Linearity	± 3%		
Mechanical Angle	Start point < 79.5° , End point > 187.5°		
Electrical Angle	Start point 80.5° +/- 1°, End point > 185.5° +/- 1°		
Spring Force	20 to 120 mNm		
Environmental/Mechanical			
Temperature	Operating	Celsius	-40° to +140°
Mechanical Shock	10ms Half Sine	Max.	50g
Sine Vibration	20 – 2500Hz	Max.	40g

## Littelfuse

Website: [www.littelfuse.com](http://www.littelfuse.com)  
 Sales Support: [ALL\\_Autosensors\\_Sales@littelfuse.com](mailto:ALL_Autosensors_Sales@littelfuse.com)  
 Technical Support: [ALL\\_Autosensors\\_Tech@littelfuse.com](mailto:ALL_Autosensors_Tech@littelfuse.com)

Information provided by Littelfuse is believed to be accurate and reliable.

All rights reserved. Trademarks and registered trademarks are the property of their respective owners.

Littelfuse products are designed for specific applications and should not be used for any purpose (including, without limitation, automotive applications) not expressly set forth in applicable Littelfuse product documentation. Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse product documentation. Littelfuse shall not be liable for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse product documentation.