IXYS

High Voltage IGBTs

IXGK100N170
IXGX100N170

V_{CES} = 1700V
I_{C90} = 100A
$V_{CE(sat)}$ ≤ 3.0V



TO-264 (IXGK)



PLUS247 (IXGX)



G = Gate
C = Collector
E = Emitter
Tab = Collector

Symbol	Test Conditions	Maximum Ratings	
V_{CES}	T_J = 25°C to 150°C	1700	V
V_{CGR}	T_J = 25°C to 150°C, R_{GE} = 1MΩ	1700	V
V_{GES}	Continuous	±20	V
V_{GEM}	Transient	±30	V
I_{C25}	T_C= 25°C (Chip Capability)	170	A
I_{LRMS}	Terminal Current Limit	160	A
I_{C90}	T_C = 90°C	100	A
I_{CM}	T_C = 25°C, 1ms	600	A
SSOA (RBSOA)	V_{GE} = 15V, T_{VJ} = 125°C, R_G = 1Ω Clamped Inductive Load	I_{CM} = 200 @0.8 • V_{CES}	A
t_{sc} (SCSOA)	V_{GE}= 15V, V_{CE} = 1250V, T_J = 125°C R_G = 10Ω, Non Repetitive	10	μs
P_C	T_C = 25°C	830	W
T_J		-55 ... +150	°C
T_{JM}		150	°C
T_{stg}		-55 ... +150	°C
T_L	Maximum Lead Temperature for Soldering	300	°C
T_{SOLD}	1.6 mm (0.062in.) from Case for 10s	260	°C
M_d	Mounting Torque (TO-264)	1.13/10	Nm/lb.in.
F_C	Mounting Force (PLUS247)	20..120 /4.5..27	N/lb.
Weight	TO-264	10	g
	PLUS247	6	g

Symbol	Test Conditions (T_J = 25°C, Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
BV_{CES}	I_C = 3mA, V_{GE} = 0V	1700			V
$V_{GE(th)}$	I_C = 8mA, V_{CE} = V_{GE}	3.0		5.0	V
I_{CES}	V_{CE} = V_{CES}, V_{GE} = 0V			50	μA
	T_J = 125°C			3	mA
I_{GES}	V_{CE} = 0V, V_{GE} = ±20V			±200	nA
$V_{CE(sat)}$	I_C = 100A, V_{GE} = 15V, Note 1		2.5	3.0	V

Features

- Optimized for Low Conduction and Switching Losses
- Short Circuit Capability
- High Current Handling Capability

Advantages

- High Power Density
- Low Gate Drive Requirement

Applications

- Power Inverters
- UPS
- Motor Drives
- SMPS
- PFC Circuits
- Welding Machines

© 2012 IXYS CORPORATION, All Rights Reserved

Symbol	Test Conditions (T_J = 25°C Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.
g_{fs}	I_C = 60A, V_{CE} = 10V, Note 1	36	64	S
C_{ies}	V_{CE} = 25V, V_{GE} = 0V, f = 1MHz		9200	pF
C_{oes}			455	pF
C_{res}			150	pF
Q_g	I_C = 100A, V_{GE} = 15V, V_{CE} = 0.5 • V_{CES}		425	nC
Q_{ge}			65	nC
Q_{gc}			186	nC
$t_{d(on)}$	**Resistive load, T_J = 25°C**		35	ns
t_r	I_C = 100A, V_{GE} = 15V		192	ns
$t_{d(off)}$	V_{CE} = 0.5 • V_{CES}, R_G = 1Ω		285	ns
t_f			395	ns
$t_{d(on)}$	**Resistive load, T_J = 125°C**		35	ns
t_r	I_C = 100A, V_{GE} = 15V		250	ns
$t_{d(off)}$	V_{CE} = 0.5 • V_{CES}, R_G = 1Ω		285	ns
t_f			435	ns
R_{thJC}				0.15 °C/W
R_{thCS}			0.15	°C/W

Note: 1. Pulse test, t ≤ 300μs, duty cycle, d ≤ 2%.

TO-264 Outline



Terminals: 1 = Gate
2,4 = Collector
3 = Emitter

SYM	INCHES MIN	MAX	MILLIMETERS MIN	MAX
A	.185	.209	4.70	5.31
A1	.102	.118	2.59	3.00
b	.037	.055	0.94	1.40
b1	.087	.102	2.21	2.59
b2	.110	.126	2.79	3.20
c	.017	.029	0.43	0.74
D	1.007	1.047	25.58	26.59
E	.760	.799	19.30	20.29
e	.215BSC		5.46 BSC	
J	.000	.010	0.00	0.25
K	.000	.010	0.00	0.25
L	.779	.842	19.79	21.39
L1	.087	.102	2.21	2.59
ØP	.122	.138	3.10	3.51
Q	.240	.256	6.10	6.50
Q1	.330	.346	8.38	8.79
ØR	.155	.187	3.94	4.75
ØR1	.085	.093	2.16	2.36
S	.243	.253	6.17	6.43

PLUS247™ Outline



Terminals: 1 - Gate
2 - Collector
3 - Emitter

Dim.	Millimeter Min.	Max.	Inches Min.	Max.
A	4.83	5.21	.190	.205
A_1	2.29	2.54	.090	.100
A_2	1.91	2.16	.075	.085
b	1.14	1.40	.045	.055
b_1	1.91	2.13	.075	.084
b_2	2.92	3.12	.115	.123
C	0.61	0.80	.024	.031
D	20.80	21.34	.819	.840
E	15.75	16.13	.620	.635
e	5.45 BSC		.215 BSC	
L	19.81	20.32	.780	.800
L1	3.81	4.32	.150	.170
Q	5.59	6.20	.220	0.244
R	4.32	4.83	.170	.190

IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: 4,835,592 4,931,844 5,049,961 5,237,481 6,162,665 6,404,065 B1 6,683,344 6,727,585 7,005,734 B2 7,157,338B2 4,850,072 5,017,508 5,063,307 5,381,025 6,259,123 B1 6,534,343 6,710,405 B2 6,759,692 7,063,975 B2 4,881,106 5,034,796 5,187,117 5,486,715 6,306,728 B1 6,583,505 6,710,463 6,771,478 B2 7,071,537

Fig. 1. Output Characteristics @ T_J = 25ºC



Fig. 2. Extended Output Characteristics @ T_J = 25ºC



Fig. 3. Output Characteristics @ T_J = 125ºC



Fig. 4. Dependence of $V_{CE(sat)}$ on Junction Temperature



Fig. 5. Collector-to-Emitter Voltage vs. Gate-to-Emitter Voltage



Fig. 6. Input Admittance



© 2012 IXYS CORPORATION, All Rights Reserved

Fig. 7. Transconductance



Fig. 8. Gate Charge



Fig. 9. Reverse-Bias Safe Operating Area



Fig. 10. Capacitance



Fig. 11. Maximum Transient Thermal Impedance



IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

Fig. 12. Resistive Turn-on Rise Time vs. Junction Temperature



Fig. 13. Resistive Turn-on Rise Time vs. Collector Current



Fig. 14. Resistive Turn-on Switching Times vs. Gate Resistance



Fig. 15. Resistive Turn-off Switching Times vs. Junction Temperature



Fig. 16. Resistive Turn-off Switching Times vs. Collector Current



Fig. 17. Resistive Turn-off Switching Times vs. Gate Resistance



© 2012 IXYS CORPORATION, All Rights Reserved

IXYS
A Littelfuse Technology

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.