


### High Voltage Power MOSFET w/ Extended FBSOA

### IXTK5N250 IXTX5N250

N-Channel Enhancement Mode  
Avalanche Rated  
Guaranteed FBSOA




$$\begin{aligned} V_{DSS} &= 2500V \\ I_{D25} &= 5A \\ R_{DS(on)} &\leq 8.8\Omega \end{aligned}$$


| Symbol     | Test Conditions                                                   | Maximum Ratings   |                  |
|------------|-------------------------------------------------------------------|-------------------|------------------|
| $V_{DSS}$  | $T_J = 25^\circ\text{C to } 150^\circ\text{C}$                    | 2500              | V                |
| $V_{DGR}$  | $T_J = 25^\circ\text{C to } 150^\circ\text{C}, R_{GS} = 1M\Omega$ | 2500              | V                |
| $V_{GSS}$  | Continuous                                                        | $\pm 30$          | V                |
| $V_{GSM}$  | Transient                                                         | $\pm 40$          | V                |
| $I_{D25}$  | $T_C = 25^\circ\text{C}$                                          | 5                 | A                |
| $I_{DM}$   | $T_C = 25^\circ\text{C}$ , Pulse Width Limited by $T_{JM}$        | 20                | A                |
| $I_A$      | $T_C = 25^\circ\text{C}$                                          | 2.5               | A                |
| $E_{AS}$   | $T_C = 25^\circ\text{C}$                                          | 2.5               | J                |
| $P_D$      | $T_C = 25^\circ\text{C}$                                          | 960               | W                |
| $T_J$      |                                                                   | -55 to +150       | $^\circ\text{C}$ |
| $T_{JM}$   |                                                                   | 150               | $^\circ\text{C}$ |
| $T_{stg}$  |                                                                   | -55 to +150       | $^\circ\text{C}$ |
| $T_L$      | 1.6mm (0.062 in.) from Case for 10s                               | 300               | $^\circ\text{C}$ |
| $T_{SOLD}$ | Plastic Body for 10s                                              | 260               | $^\circ\text{C}$ |
| $M_d$      | Mounting Torque (TO-264)                                          | 1.13/10           | Nm/lb.in.        |
| $F_C$      | Mounting Force (PLUS247)                                          | 20..120 / 4.5..27 | N/lb.            |
| Weight     | TO-264                                                            | 10                | g                |
|            | PLUS247                                                           | 6                 | g                |

| Symbol       | Test Conditions<br>( $T_J = 25^\circ\text{C}$ , Unless Otherwise Specified) | Characteristic Values |      |                          |
|--------------|-----------------------------------------------------------------------------|-----------------------|------|--------------------------|
|              |                                                                             | Min.                  | Typ. | Max.                     |
| $BV_{DSS}$   | $V_{GS} = 0V, I_D = 1mA$                                                    | 2500                  |      | V                        |
| $V_{GS(th)}$ | $V_{DS} = V_{GS}, I_D = 1mA$                                                | 2.0                   |      | 5.0 V                    |
| $I_{GSS}$    | $V_{GS} = \pm 30V, V_{DS} = 0V$                                             |                       |      | $\pm 200$ nA             |
| $I_{DSS}$    | $V_{DS} = 2kV, V_{GS} = 0V$<br>$T_J = 125^\circ\text{C}$                    |                       |      | 50 $\mu\text{A}$<br>4 mA |
| $R_{DS(on)}$ | $V_{GS} = 10V, I_D = 0.5 \cdot I_{D25}$ , Note 1                            |                       |      | 8.8 $\Omega$             |

TO-264 (IXTK)



PLUS247 (IXTX)



G = Gate      D = Drain  
S = Source      Tab = Drain

#### Features

- Avalanche Rated
- Fast Intrinsic Diode
- Guaranteed FBSOA at  $75^\circ\text{C}$
- Low Package Inductance

#### Advantages

- Easy to Mount
- Space Savings

#### Applications

- High Voltage Power Supplies
- Capacitor Discharge
- Pulse Circuits

| Symbol       | Test Conditions<br>( $T_J = 25^\circ\text{C}$ , Unless Otherwise Specified)                                                                        | Characteristic Values |      |                    |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|------|--------------------|
|              |                                                                                                                                                    | Min.                  | Typ. | Max.               |
| $g_{fs}$     | $V_{DS} = 50\text{V}$ , $I_D = 0.5 \cdot I_{D25}$ , Note 1                                                                                         | 3.0                   | 4.5  | 6.0                |
| $C_{iss}$    | $V_{GS} = 0\text{V}$ , $V_{DS} = 25\text{V}$ , $f = 1\text{MHz}$                                                                                   |                       | 8560 | pF                 |
| $C_{oss}$    |                                                                                                                                                    |                       | 315  | pF                 |
| $C_{rss}$    |                                                                                                                                                    |                       | 90   | pF                 |
| $t_{d(on)}$  | <b>Resistive Switching Times</b><br>$V_{GS} = 10\text{V}$ , $V_{DS} = 0.5 \cdot V_{DSS}$ , $I_D = 0.5 \cdot I_{D25}$<br>$R_G = 1\Omega$ (External) |                       | 33   | ns                 |
| $t_r$        |                                                                                                                                                    |                       | 20   | ns                 |
| $t_{d(off)}$ |                                                                                                                                                    |                       | 90   | ns                 |
| $t_f$        |                                                                                                                                                    |                       | 44   | ns                 |
| $Q_{g(on)}$  | $V_{GS} = 10\text{V}$ , $V_{DS} = 1000\text{V}$ , $I_D = 0.5 \cdot I_{D25}$                                                                        |                       | 200  | nC                 |
| $Q_{gs}$     |                                                                                                                                                    |                       | 28   | nC                 |
| $Q_{gd}$     |                                                                                                                                                    |                       | 70   | nC                 |
| $R_{thJC}$   |                                                                                                                                                    |                       | 0.13 | $^\circ\text{C/W}$ |
| $R_{thCS}$   |                                                                                                                                                    |                       |      | $^\circ\text{C/W}$ |

## Safe Operating Area Specification

| Symbol | Test Conditions                                                                               | Characteristic Values |      |      |
|--------|-----------------------------------------------------------------------------------------------|-----------------------|------|------|
|        |                                                                                               | Min.                  | Typ. | Max. |
| SOA    | $V_{DS} = 2000\text{V}$ , $I_D = 0.11\text{A}$ , $T_C = 75^\circ\text{C}$ , $t_p = 3\text{s}$ | 220                   |      | W    |

## Source-Drain Diode


| Symbol   | Test Conditions<br>( $T_J = 25^\circ\text{C}$ , Unless Otherwise Specified)    | Characteristic Values |      |               |
|----------|--------------------------------------------------------------------------------|-----------------------|------|---------------|
|          |                                                                                | Min.                  | Typ. | Max.          |
| $I_S$    | $V_{GS} = 0\text{V}$                                                           |                       |      | 5             |
| $I_{SM}$ | Repetitive, Pulse Width Limited by $T_{JM}$                                    |                       |      | 20            |
| $V_{SD}$ | $I_F = I_S$ , $V_{GS} = 0\text{V}$ , Note 1                                    |                       |      | 1.5           |
| $t_{rr}$ | $I_F = 2.5\text{A}$ , $-di/dt = 100\text{A}/\mu\text{s}$ , $V_R = 100\text{V}$ |                       | 1.2  | $\mu\text{s}$ |

Note: 1. Pulse test,  $t \leq 300\mu\text{s}$ , duty cycle,  $d \leq 2\%$ .

## ADVANCE TECHNICAL INFORMATION


The product presented herein is under development. The Technical Specifications offered are derived from a subjective evaluation of the design, based upon prior knowledge and experience, and constitute a "considered reflection" of the anticipated result. IXYS reserves the right to change limits, test conditions, and dimensions without notice.

## TO-264 Outline



| Dim. | Millimeter |       | Inches   |       |
|------|------------|-------|----------|-------|
|      | Min.       | Max.  | Min.     | Max.  |
| A    | 4.82       | 5.13  | .190     | .202  |
| A1   | 2.54       | 2.89  | .100     | .114  |
| A2   | 2.00       | 2.10  | .079     | .083  |
| b    | 1.12       | 1.42  | .044     | .056  |
| b1   | 2.39       | 2.69  | .094     | .106  |
| b2   | 2.90       | 3.09  | .114     | .122  |
| c    | 0.53       | 0.83  | .021     | .033  |
| D    | 25.91      | 26.16 | 1.020    | 1.030 |
| E    | 19.81      | 19.96 | .780     | .786  |
| e    | 5.46 BSC   |       | .215 BSC |       |
| J    | 0.00       | 0.25  | .000     | .010  |
| K    | 0.00       | 0.25  | .000     | .010  |
| L    | 20.32      | 20.83 | .800     | .820  |
| L1   | 2.29       | 2.59  | .090     | .102  |
| P    | 3.17       | 3.66  | .125     | .144  |
| Q    | 6.07       | 6.27  | .239     | .247  |
| Q1   | 8.38       | 8.69  | .330     | .342  |
| R    | 3.81       | 4.32  | .150     | .170  |
| R1   | 1.78       | 2.29  | .070     | .090  |
| S    | 6.04       | 6.30  | .238     | .248  |
| T    | 1.57       | 1.83  | .062     | .072  |

## PLUS247™ Outline




| Dim. | Millimeter |       | Inches   |      |
|------|------------|-------|----------|------|
|      | Min.       | Max.  | Min.     | Max. |
| A    | 4.83       | 5.21  | .190     | .205 |
| A1   | 2.29       | 2.54  | .090     | .100 |
| A2   | 1.91       | 2.16  | .075     | .085 |
| b    | 1.14       | 1.40  | .045     | .055 |
| b1   | 1.91       | 2.13  | .075     | .084 |
| b2   | 2.92       | 3.12  | .115     | .123 |
| C    | 0.61       | 0.80  | .024     | .031 |
| D    | 20.80      | 21.34 | .819     | .840 |
| E    | 15.75      | 16.13 | .620     | .635 |
| e    | 5.45 BSC   |       | .215 BSC |      |
| L    | 19.81      | 20.32 | .780     | .800 |
| L1   | 3.81       | 4.32  | .150     | .170 |
| Q    | 5.59       | 6.20  | .220     | .244 |
| R    | 4.32       | 4.83  | .170     | .190 |


IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

|                                                                                  |           |           |           |           |              |              |              |              |              |              |
|----------------------------------------------------------------------------------|-----------|-----------|-----------|-----------|--------------|--------------|--------------|--------------|--------------|--------------|
| IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: | 4,835,592 | 4,931,844 | 5,049,961 | 5,237,481 | 6,162,665    | 6,404,065 B1 | 6,683,344    | 6,727,585    | 7,005,734 B2 | 7,157,338 B2 |
|                                                                                  | 4,850,072 | 5,017,508 | 5,063,307 | 5,381,025 | 6,259,123 B1 | 6,534,343    | 6,710,405 B2 | 6,759,692    | 7,063,975 B2 |              |
|                                                                                  | 4,881,106 | 5,034,796 | 5,187,117 | 5,486,715 | 6,306,728 B1 | 6,583,505    | 6,710,463    | 6,771,478 B2 | 7,071,537    |              |


**Fig. 1. Output Characteristics @  $T_J = 25^\circ\text{C}$**




**Fig. 2. Output Characteristics @  $T_J = 125^\circ\text{C}$**




**Fig. 3.  $R_{DS(on)}$  Normalized to  $I_D = 2.5\text{A}$  Value vs. Junction Temperature**




**Fig. 4.  $R_{DS(on)}$  Normalized to  $I_D = 2.5\text{A}$  Value vs. Drain Current**




**Fig. 5. Maximum Drain Current vs. Case Temperature**




**Fig. 6. Input Admittance**




**Fig. 7. Transconductance**




**Fig. 8. Forward Voltage Drop of Intrinsic Diode**




**Fig. 9. Gate Charge**



**Fig. 10. Capacitance**



**Fig. 11. Forward-Bias Safe Operating Area**  
**@  $T_C = 25^\circ\text{C}$**



**Fig. 12. Forward-Bias Safe Operating Area**  
**@  $T_C = 75^\circ\text{C}$**





Fig. 13. Maximum Transient Thermal Impedance





---

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).