





MCR70xA Series



Pin Out



Description

The MCR70xA Series is a PNP component designed for high volume, low cost consumer applications such as temperature, light and speed control; process and remote control; and warning systems where reliability of operation is critical.

Features


- Small Size
- Passivated Die Surface for Reliability and Uniformity
- Low Level Triggering and Holding Characteristics
- Recommend Electrical Replacement for C106
- Surface Mount Package – Case 369C
- To Obtain “DPAK” in Straight Lead Version (Shipped in Sleeves): Add ‘1’ Suffix to Component Number, i.e., MCR706A1
- UL Recognized compound meeting flammability rating V-0.
- ESD Ratings: Human Body Model, 3B > 8000 V Machine Model, C > 400 V
- Pb-Free Packages are Available

Additional Information



Resources

Functional Diagram



Maximum Ratings ($T_J = 25^\circ\text{C}$ unless otherwise noted)

| Rating | Symbol | Value | Unit |
|---|---|-------------------|--------------------|
| Peak Repetitive Off-State Voltage (Note 1) ($T_C = -40$ to $+110^\circ\text{C}$, Sine Wave, 50 to 60 Hz, $R_{GK} = 1\text{ k}\Omega$) | MCR703A MCR706A MCR708A V_{DRM} V_{RRM} | 100 400 600 | V |
| Peak Non-Repetitive Off-State Voltage (180° Conduction Angles; $T_C = 85^\circ\text{C}$) | MCR703A MCR706A MCR708A V_{DSM} | 150 450 650 | V |
| On-State RMS Current (180° Conduction Angles; $T_C = 90^\circ\text{C}$) | $I_{T(RMS)}$ | 4.0 | A |
| Average On-State Current (180° Conduction Angles) | $T_C = -40$ to $+90^\circ\text{C}$ $T_C = +100^\circ\text{C}$ $I_{T(AV)}$ | 2.6 1.6 | A |
| Non-Repetitive Surge Current (1/2 Cycle, Sine Wave 60 Hz, $T_J = 110^\circ\text{C}$) (1/2 Cycle, Sine Wave 1.5 ms, $T_J = 110^\circ\text{C}$) | I_{TSM} | 25 35 | A |
| Circuit Fusing Consideration ($t = 8.3\text{ ms}$) | I^2t | 2.6 | A ² sec |
| Forward Peak Gate Power (Pulse Width $\leq 1.0\text{ }\mu\text{sec}$, $T_C = 90^\circ\text{C}$) | P_{GM} | 0.5 | W |
| Forward Peak Gate Current (Pulse Width $\leq 1.0\text{ }\mu\text{sec}$, $T_C = 90^\circ\text{C}$) | I_{GM} | 0.2 | A |
| Forward Average Gate Power ($t = 8.3\text{ ms}$, $T_C = 90^\circ\text{C}$) | $P_{G(AV)}$ | 0.1 | W |
| Operating Junction Temperature Range | T_J | -40 to +110 | $^\circ\text{C}$ |
| Storage Temperature Range | T_{STG} | -40 to +150 | $^\circ\text{C}$ |

Stresses exceeding Maximum Ratings may damage the Component. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect Component reliability.

1. V_{DRM} and V_{RRM} for all types can be applied on a continuous basis. Ratings apply for zero or negative gate voltage; however, positive gate voltage shall not be applied concurrent with negative potential on the anode. Blocking voltages shall not be tested with a constant current source such that the voltage ratings of the Components are exceeded.

Thermal Characteristics*

| Rating | Symbol | Value | Unit |
|---|-----------------|-------|---------------------------|
| Thermal Resistance, Junction-to-Case | $R_{\theta JC}$ | 3.0 | $^\circ\text{C}/\text{W}$ |
| Thermal Resistance, Junction-to-Ambient (Note 2) | $R_{\theta JA}$ | 80 | |
| Maximum Lead Temperature for Soldering Purposes 1/8" from Case for 10 Seconds | T_L | 260 | $^\circ\text{C}$ |

2. Case 369C when surface mounted on minimum pad sizes recommended.

Electrical Characteristics - OFF ($T_J = 25^\circ\text{C}$ unless otherwise noted)

| Characteristic | Symbol | Min | Typ | Max | Unit |
|--|---|-----|-----|-----------|---------------|
| Peak Repetitive Forward or Reverse Blocking Current ($V_{AK} = \text{Rated } V_{DRM}$ or V_{RRM} ; $R_{GK} = 1\text{ k}\Omega$) | $T_J = 25^\circ\text{C}$ $T_J = 110^\circ\text{C}$ I_{DRM} I_{RRM} | - | - | 10 200 | μA |

Electrical Characteristics - ON ($T_J = 25^\circ\text{C}$ unless otherwise noted)

| Characteristic | Symbol | Min | Typ | Max | Unit |
|--|---|-----|------|------------|---------------|
| Peak Forward "On" Voltage ($I_{TM} = 8.2\text{ A}$ Peak, Pulse Width = 1 to 2 ms, 2% Duty Cycle) | V_{TM} | - | - | 2.2 | V |
| Gate Trigger Current (Continuous dc) (Note 3) ($V_{AK} = 12\text{ V}$; $R_L = 24\text{ }\Omega$) | $T_J = 25^\circ\text{C}$ $T_J = -40^\circ\text{C}$ I_{GT} | - | 25 | 75 300 | μA |
| Gate Trigger Voltage (Continuous dc) (Note 3) ($V_{AK} = 12\text{ V}$; $R_L = 24\text{ }\Omega$) | $T_J = 25^\circ\text{C}$ $T_J = -40^\circ\text{C}$ V_{GT} | - | - | 0.8 1.0 | V |
| Gate Non-Trigger Voltage (Note 3) ($V_{AK} = 12\text{ Vdc}$; $R_L = 100\text{ }\Omega$; $T_C = 110^\circ$) | V_{GD} | 0.2 | - | - | V |
| Holding Current ($V_{AK} = 12\text{ Vdc}$, $R_{GK} = 1\text{ k}\Omega$) $T_C = 25^\circ\text{C}$ (Initiating Current = 20 mA) $T_C = -40^\circ\text{C}$ | I_H | - | - | 5.0 10 | mA |
| Peak Reverse Gate Blocking Voltage ($I_{GR} = 10\text{ }\mu\text{A}$) | V_{RGM} | 10 | 12.5 | 18 | V |
| Peak Reverse Gate Blocking Current ($V_{GR} = 10\text{ V}$) | I_{RGM} | - | - | 1.2 | μA |
| Total Turn-On Time (Source Voltage = 12 V, $R_S = 6\text{ k}\Omega$) ($I_{TM} = 8.2\text{ A}$, $I_{GT} = 2\text{ mA}$, Rated V_{DRM}) (Rise Time = 20 ns, Pulse Width = 10 μs) | t_{GT} | - | 2.0 | - | μs |

Dynamic Characteristics*

| Characteristic | Symbol | Min | Typ | Max | Unit |
|---|--------|-----|-----|-----|------------------|
| Critical Rate of Rise of Off-State Voltage ($V_D = \text{Rated } V_{DRM}$, $R_{GK} = 1 \text{ k}\Omega$, Exponential Waveform, Gate Open, $T_c = 110^\circ\text{C}$) | dv/dt | – | 10 | – | V/ μs |
| Repetitive Critical Rate of Rise of On-State Current (Cf = 60 Hz, $I_{PK} = 30 \text{ A}$, PW = 100 μs , diG/dt = 1 A/ μs) | di/dt | – | – | 100 | A/ μs |

3. RGK current not included in measurement.

Voltage Current Characteristic of SCR

| Symbol | Parameter |
|-----------|---|
| V_{DRM} | Peak Repetitive Forward Off State Voltage |
| I_{DRM} | Peak Forward Blocking Current |
| V_{RRM} | Peak Repetitive Reverse Off State Voltage |
| I_{RRM} | Peak Reverse Blocking Current |
| V_{TM} | Maximum On State Voltage |
| I_H | Holding Current |




Figure 1. RMS Current Derating




Figure 2. On-State Power Dissipation




Figure 3. On-State Characteristics




Figure 4. Transient Thermal Response




Figure 5. Typical Gate Trigger Current vs Junction Temperature




Figure 6. Typical Gate Trigger Voltage vs Junction Temperature




Figure 7. Typical Holding Current vs Junction Temperature







Figure 8. Typical Latching Current vs Junction Temperature



Dimensions



Soldering Footprint




| Dim | Inches | | Millimeters | |
|-----|--------|-------|-------------|-------|
| | Min | Max | Min | Max |
| A | 0.087 | 0.094 | 2.20 | 2.40 |
| A1 | 0.000 | 0.005 | 0.00 | 0.12 |
| b | 0.022 | 0.030 | 0.55 | 0.75 |
| b2 | 0.026 | 0.033 | 0.65 | 0.85 |
| b3 | 0.209 | 0.217 | 5.30 | 5.50 |
| c | 0.019 | 0.023 | 0.49 | 0.59 |
| c2 | 0.019 | 0.023 | 0.49 | 0.59 |
| D | 0.213 | 0.224 | 5.40 | 5.70 |
| E | 0.252 | 0.260 | 6.40 | 6.60 |
| e | 0.091 | | 2.30 | |
| H | 0.374 | 0.406 | 9.50 | 10.30 |
| L | 0.058 | 0.070 | 1.47 | 1.78 |
| L1 | 0.114 | | 2.90 | |
| L2 | 0.019 | 0.023 | 0.49 | 0.59 |
| L3 | 0.053 | 0.065 | 1.35 | 1.65 |
| L4 | 0.028 | 0.039 | 0.70 | 1.00 |
| Z | 0.154 | - | 3.90 | - |

1. Dimensioning and Tolerancing per ANSI Y14.5M, 1982.
2. Controlling Dimension: Inch.

STYLE 6:
PIN 1. GATE
2. ANODE
3. CATHODE
4. ANODE

Dimensions

DPAK-3
Case 369D-01
Issue B




| Dim | Inches | | Millimeters | |
|-----|--------|-------|-------------|------|
| | Min | Max | Min | Max |
| A | 0.213 | 0.224 | 5.40 | 5.70 |
| B | 0.252 | 0.260 | 6.40 | 6.60 |
| C | 0.087 | 0.094 | 2.20 | 2.40 |
| D | 0.024 | 0.030 | 0.60 | 0.75 |
| E | 0.022 | 0.026 | 0.55 | 0.65 |
| F | 0.031 | 0.039 | 0.78 | 0.98 |
| G | 0.091 | | 2.30 | |
| H | 0.046 | 0.050 | 1.18 | 1.28 |
| J | 0.019 | 0.023 | 0.49 | 0.59 |
| K | 0.291 | 0.315 | 7.40 | 8.00 |
| R | 0.209 | 0.217 | 5.30 | 5.50 |
| S | 0.063 | | 1.60 | |
| V | 0.053 | 0.065 | 1.35 | 1.65 |
| Z | 0.150 | | 3.80 | |



1. Dimensioning and Tolerancing per ANSI Y14.5M, 1982.
2. Controlling Dimension: Inch.

STYLE 6:
PIN 1: GATE
2: ANODE
3: CATHODE
4: ANODE


Part Marking System



DPAK
Case 369C
Style 6



DPAK-3
Case 369D
Style 6



x =D, M, or N
Y =Year
M =Month
A =Assembly Site
XX =Lot Serial Code
G =Pb-Free Package

| Pin Assignment | |
|----------------|---------|
| 1 | Gate |
| 2 | Anode |
| 3 | Cathode |
| 4 | Anode |

Ordering Information

| Component | Package | | Shipping |
|------------|---------|-------------------|---------------------|
| MCR703AT4 | DPAK | 369C | 2500 Tape & Reel |
| MCR703AT4G | | 369C (Pb-Free) | |
| MCR706AT4 | | 369C | |
| MCR706AT4G | | 369C (Pb-Free) | |
| MCR708A | DPAK-3 | 369C | 4000 Units/ Box |
| MCR708AG | | 369C (Pb-Free) | |
| MCR708A1 | | 369D | |
| MCR708A1G | | 369D (Pb-Free) | |
| MCR708AT4 | DPAK | 369C | 2500 Tape & Reel |
| MCR708AT4G | | 369C (Pb-Free) | |