

Specification Status: Released

Marking:

XX 60 R 05 HB

Week of Manufacture
Per Manufacturer's
Lot numbering system
Eg. H = Second half of 2004; B = week 2

Surge Rating
05: 5kA

Product Family

Voltage Designator
60: 600V

Manufacturer's Mark




TABLE I. ELECTRICAL CHARACTERISTICS

DC Sparkover Voltage*	Impulse Sparkover Voltage		Insulation Resistance	Capacitance	AC Discharge Current, 50 Hz	Impulse Discharge Current 10/1000 μ s	Impulse Discharge Current, 8/20 μ s
@ 100V/s	@100V/ μ s	@1000V/ μ s	@100V _{DC}	@1MHz	Multiple Hits (1s duration: 10 hits)	300 hits (150hits for each polarity)	10 hits (5hits for each polarity)
350V $\pm$ 20%	≤ 900 V	≤ 1000 V	$\geq 10,000$ M Ω	<1.0pF	5Arms	100A	5kA

*In ionized mode
Testing methods and specifications referring to ITU-T K.12

General Characteristics:

No Radioactive Materials
Storage temperature: -40°C ... +90°C
Operating temperature: -40°C ... +90°C
Electrode: Ni Plating
Lead Material: Tin Plated

Agency Recognitions: UL Recognized
Precedence: This specification takes precedence over documents referenced herein
Effectivity: Reference documents shall be the issue in effect on the date of invitation for bid
CAUTION: Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame

Materials Information

ROHS Compliant

Directive 2002/95/EC
Compliant

ELV Compliant

Directive 2000/53/EC
Compliant

Pb-Free



Gas Discharge Tube

Over-Voltage Protection Device

PRODUCT: GTCS25-351M-R05

DOCUMENT: SCD28972
REV LETTER: A
REV DATE: JULY 26, 2016
PAGE NO.: 2 OF 2

Littelfuse products are not designed for, and shall not be used for, any purpose (including, without limitation, automotive, military, aerospace, medical, life-saving, life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable Littelfuse product, documentation. Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse documentation. Littelfuse shall not be liable for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse documentation. The sale and use of Littelfuse products is subject to Littelfuse Terms and Conditions of Sale, unless otherwise agreed by Littelfuse.