

M-284 SERIES BATTERY DISCONNECT SWITCHES



M-284

Features and Benefits

- Marine grade, brass case
- Sealed options between shaft and insulator
- UL listed P/Ns
- Compact design
- Silver plated contact options for high conductivity and low contact resistance

Specifications Overview

Amperage:	175A
Voltage Rating:	36V DC
Circuitry:	SPST
Housing:	Brass

Applications

- Commercial Marine
- Boating
- Emergency Vehicles
- Heavy Duty Truck
- Bus/Transit

Recommended Products



**24505 & 24505-01
Lockout Lever Kit**

Description

M-284 Series Battery Disconnect Switches are marine grade, manual, master disconnect switches. The M-284 switches shown are 175A, 36V Single Pole, Single Throw (SPST) and can be used to disconnect the battery from the vehicle electrical system. The shown switches have a 1000A intermittent current rating for 15 sec ON, 5 min OFF. Disconnecting the battery from the electrical system prevents potential thermal events and ensures system shut down during maintenance or emergency. Battery disconnect switches also prevent parasitic loads from draining the battery during inactivity.

Web Resources

Download 2D print and technical resources at:
littelfuse.com/M284

Ordering Information

PART NUMBER	DESCRIPTION	MAX INPUT CURRENT	CONTACTS	UL LISTED
M-284 *	Marine Grade Battery Disconnect Switch	1000A intermittent for 15 sec ON, 5 min OFF	Two copper studs (3/8-24)	
M-284-01 *	Marine Grade Battery Disconnect Switch	800A intermittent for 15 sec ON, 5 min OFF	Two silver laminated brass studs (3/8-24)	•
M-284-02 *	Marine Grade Battery Disconnect Switch, O-ring seal in operating shaft, gasket-sealed terminal insulator	1000A intermittent for 15 sec ON, 5 min OFF	Two silvered copper studs (3/8-24)	
M-284-09-BP	Marine Grade Battery Disconnect Switch w/Faceplate Blister Pack	1000A intermittent for 15 sec ON, 5 min OFF	Two silvered copper studs (3/8-24)	

* Box and Retail Blister Pack Available



Visit Littelfuse.com for the most up-to-date product information. Littelfuse products are designed for specific applications and should not be used for any purpose (including, without limitation, automotive applications) not expressly set forth in applicable Littelfuse product documentation. Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse product documentation. Littelfuse shall not be liable for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse product documentation.