



## IZLT2.E70164 Fuseholders, Cartridge Fuse - Component

If you notice a change to your IZLT2 Listing Card, click [here](#) to learn more.

[Page Bottom](#)

### Fuseholders, Cartridge Fuse - Component

[See General Information for Fuseholders, Cartridge Fuse - Component](#)


#### LITTELFUSE WICKMANN WERKE

E70164

8755 W HIGGINS RD  
SUITE 500  
CHICAGO, IL 60631 USA

Cat. No.	Voltage Rating (V)	Current Rating (A)	Withstand Rating RMS Symmetrical	Fuse Class or Size
<b>518 0000 1009</b>	500ac/dc	10	-	-
<b>653 All catalog numbers may have optional Prefix 19.</b>	250ac	16	-	-
<b>655 All catalog numbers may have optional Prefix 19.</b>	250ac	16	-	-
<b>656 0000 1009</b>	500ac/dc	16	-	5x20mm
<b>656 0000 1409</b>	500ac/dc	16	-	5x20mm
<b>658 0000 1009</b>	500ac/dc	16	-	5x20mm
<b>658 0000 1039</b>	500ac/dc	16	-	5x20mm
<b>658 0000 1109</b>	500ac/dc	16	-	5x20mm
<b>659 0000 1009</b>	500ac/dc	16	-	5x20mm
<b>660 0000 1009</b>	500ac/dc	16	-	5x20mm
<b>800-01 for use with caps. Cat. Nos. 815, 816, 835 or 837. All catalog numbers may have an optional Prefix "19".</b>				
	500ac	16	-	-
<b>801 with caps 815 and 816. All catalog numbers may have an optional Prefix 19.</b>				
	250ac	16	-	-
<b>802 with caps 815 and 816. All catalog numbers may have an optional Prefix 19.</b>				
	250ac	16	-	-
<b>803-01 for use with caps. Cat. Nos. 815, 816, 835 or 837. All catalog numbers may have an optional Prefix "19".</b>				
	500ac	16	-	-
<b>810 for use with caps. Cat. Nos. 815, 816, 835 or 837. All catalog numbers may have an optional Prefix "19".</b>				
	250ac	16	-	-
<b>811 for use with caps. Cat. Nos. 815, 816, 835 or 837. All catalog numbers may have an optional Prefix "19".</b>				
	250ac	16	-	-
<b>813 for use with caps. Cat. Nos. 815, 816, 835 or 837. All catalog numbers may have an optional Prefix "19".</b>				
	250ac	16	-	-
<b>814 for use with caps. Cat. Nos. 815, 816, 835 or 837. All catalog numbers may have an optional Prefix "19".</b>				
	250ac	16	-	-

<b>820-20 All catalog numbers may have an optional Prefix 19.</b>	250ac	16	-	-
<b>821 All catalog numbers may have an optional Prefix 19.</b>	250ac	16	-	-
<b>823 All catalog numbers may have an optional Prefix 19.</b>	250ac	16	-	-
<b>824 All catalog numbers may have an optional Prefix 19.</b>	250ac	16	-	-
<b>830 for use with caps. Cat. Nos. 815, 816, 835 or 837. All catalog numbers may have an optional Prefix "19".</b>				
	250ac	16	-	-
<b>831 for use with caps. Cat. Nos. 815, 816, 835 or 837. All catalog numbers may have an optional Prefix "19".</b>				
	250ac	16	-	-
<b>834 with cap Cat. No. 835, 835-20, or 837. All catalog numbers may have an optional Prefix 19.</b>				
	250ac	6.3	-	-
<b>850 0000 1009</b>	250ac/dc	10	-	-
<b>851 0000 1009</b>	250ac/dc	10	-	-
<b>852 0000 1009</b>	250ac/dc	12	-	-
<b>853 0000 1009</b>	250ac/dc	12	-	-
<b>855 0000 1009</b>	250ac/dc	10	-	-
<b>856 0000 1009</b>	250ac/dc	10	-	-
<b>860 0000 1009</b>	250ac/dc	20	-	-
<b>862 0000 1009</b>	250ac/dc	16	-	-
<b>870 0000 1009</b>	250ac/dc	10	-	-
<b>Cat. No. 800 with caps 815 and 816. All catalog numbers may have an optional Prefix 19.</b>				
	250ac	16	-	-
<b>Cat. Nos. 601 All catalog numbers may have optional Prefix 19.</b>	250ac	16	-	-
<b>Cat. Nos. 820 All catalog numbers may have an optional Prefix 19.</b>	250ac	16	-	-

Marking: Company name or tradename "catalog or part designation may include the optional prefix 19" or trademark  and model designation.

Last Updated on 2017-12-13

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".