

JGGS2.E358130
Fuses, Supplemental for Use in Hazardous Locations - Component

Page Bottom

Fuses, Supplemental for Use in Hazardous Locations - Component

See General Information for Fuses, Supplemental for Use in Hazardous Locations - Component

LITTELFUSE INC
 SUITE 500
 8755 W HIGGINS RD
 CHICAGO, IL 60631 USA

E358130

| Cat. No. | Size (in.) | Amps | V | Interrupting Rating (A) |
|-----------|---------------------------------|-------|--------|-------------------------|
| 259*(a)+# | 8.001 x 4.7625 (0.31 x 0.19) | 0.062 | 125Vac | 50 |
| | | 0.062 | 125Vdc | 300 |
| | | 0.125 | 125Vac | 50 |
| | | 0.125 | 125Vdc | 300 |
| | | 0.250 | 125Vac | 50 |
| | | 0.250 | 125Vdc | 300 |
| | | 0.375 | 125Vac | 50 |
| | | 0.375 | 125Vdc | 300 |
| | | 0.500 | 125Vac | 50 |
| | | 0.500 | 125Vdc | 300 |
| | | 0.750 | 125Vac | 50 |
| | | 0.750 | 125Vdc | 300 |
| | | 1.000 | 125Vac | 50 |
| | | 1.000 | 125Vdc | 300 |
| | | 3.000 | 125Vac | 50 |
| | | 3.000 | 125Vdc | 300 |
| | | 5.000 | 125Vac | 50 |
| | | 5.000 | 63Vdc | 300 |

* - May be preceded by 0.

(a) - Followed by .062, .125, .250, .375, .500, .750, 001., 003., or 005. representing current rating; followed by any alphanumeric characters representing number of pieces in package.

+ - May be followed by P which indicates the utilization of lead-free solder.

- Followed by 913.

| Cat. No. | Size (in.) | Amps | V | Interrupting Rating (A) |
|---------------|------------------|-------|------------|-------------------------|
| 305*(a)(b)(c) | 0.354 OD x 0.614 | 0.050 | 277Vac/Vdc | 1500 |
| | | 0.080 | 277Vac/Vdc | 1500 |


| | | 0.100 | 277Vac/Vdc | 1500 |
|---------------|-----------------------|-------|------------|-------------------------|
| | | 0.160 | 277Vac/Vdc | 1500 |
| | | 0.200 | 277Vac/Vdc | 1500 |
| | | 0.250 | 277Vac/Vdc | 1500 |
| | | 0.500 | 277Vac/Vdc | 1500 |
| | | 0.750 | 277Vac/Vdc | 1500 |
| Cat. No. | Size (in.) | Amps | V | Interrupting Rating (A) |
| 304*(a)(b)(c) | 0.540 x 0.237 x 0.240 | 0.050 | 277Vac/Vdc | 1500 |
| | | 0.080 | 277Vac/Vdc | 1500 |
| | | 0.100 | 277Vac/Vdc | 1500 |
| | | 0.160 | 277Vac/Vdc | 1500 |
| | | 0.200 | 277Vac/Vdc | 1500 |
| | | 0.250 | 277Vac/Vdc | 1500 |
| | | 0.500 | 277Vac/Vdc | 1500 |
| | | 0.750 | 277Vac/Vdc | 1500 |

* - May be preceded by 0.

(a) - Followed by .050, .080, .100, .160, .200, .250, .500, or .750 representing current rating.

(b) - Followed by any alphanumeric characters representing number of pieces in package.

(c) - May be followed by P which indicates the utilization of lead-free solder.

Marking: Company name or tradename "LF", catalog designation and the Recognized Component Mark  .
Last Updated on 2014-10-27

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".